



TECHNICAL MEMORANDUM

To: Ian McAllister, Ashleigh Crompton, Mike Champion,
Mark Zan and Ryan Schucroft (Woodfibre LNG) **Date:** 20 Feb 2026

From: Holly Pelletier and Cheng Kuang (Lorax) **Project #:** A633-9

Subject: PE-111578 Weekly Discharge and Compliance Report #101 for February 8 – 14

Waste Discharge Authorization (WDA) Effluent Permit PE-111578 was issued by the British Columbia Energy Regulator (BCER) to Woodfibre LNG on February 9, 2024. The associated WDA discharge and compliance monitoring program is conducted by on-site Environmental Monitors (Roe Environmental) that are sub-contracted to the civil works contractor (LB LNG). Analytical samples are submitted by Roe Environmental to ALS Environmental in Burnaby, BC, for testing. Lorax Environmental Services Ltd. (Lorax) provides water quality database management and WDA compliance reporting services to Woodfibre LNG.

This technical memorandum (Report #101) was prepared by Lorax and summarizes WDA monitoring conducted for the period of February 8 – 14. Monitoring data and pending results from prior monitoring periods available at the time of reporting are tabulated and included as appendices to this memorandum. Report #101 has been prepared to meet the requirements specified in Condition 4.2 of PE-111578:

“The Permittee shall summarize the results of the discharge and compliance monitoring program in a report that shall be submitted to the BCER weekly over the term of this permit. Reports must include suitable tabulated data. The table must include any applicable regulatory limits/guidelines e.g. permit limits, BC Water Quality Guidelines etc. Any exceedances of respective regulatory limits/guidelines must be clearly highlighted. Any missed sampling events/missing data must be identified with an explanation provided. Reporting frequency may be reduced upon a history of compliance and by written confirmation from the BCER. These reports shall be submitted to Waste.Management@bc-er.ca. A copy of the reports shall be provided to each First Nation consulted with regarding this subject permit, and also made publicly available on the Woodfibre LNG Environmental Reporting webpage.”

Site layout and water management figures and site images are included in Appendix A. Monitoring results are tabulated in Appendix B through Appendix D for contact water, treated water and receiving environment samples.

1. Current Conditions

1.1 Water Management Infrastructure

The Construction Phase of the Woodfibre LNG Export Facility commenced in October 2023. Shoring works along the foreshore areas were initiated in December 2023, and construction of water management infrastructure commenced in early 2024. Land-based construction occurs within two water management areas east and west of Mill Creek, referred to as the east and west catchments, respectively. Non-contact water is intercepted and diverted around the construction areas to Howe Sound and Mill Creek. Stormwater runoff collected within the east and west catchment areas (7.12 and 5.92 ha, respectively) is managed as site contact water and is conveyed to the East Wastewater Treatment Plant (WWTP) for treatment, or to the East and West Sedimentation Ponds for settling of suspended particulate prior to discharge. Intermittent discharge to Howe Sound from the East and West Sedimentation Ponds commenced April and October 2024, respectively.

Non-contact water from the slopes above and outside the Woodfibre LNG construction area is intercepted by diversion ditches and conveyed to Howe Sound or Mill Creek. Diversion ditches for the west catchment convey water to Mill Creek at station OUT-06, or to Howe Sound at station OUT-02 (Appendix A, Figure 1). During heavy precipitation, non-contact water is also conveyed to Howe Sound via station OUT-01. East of Mill Creek, non-contact water is intercepted and diverted around the east catchment along pre-existing road ditches that flow to East Creek or Mill Creek and through Outfall 13 (OUT-13). The diversion ditch connected to Outfall 11 (OUT-11) is not yet constructed; therefore, Outfall 11 is not in use. The lower reach of East Creek discharges to Howe Sound through Outfall 12 (OUT-12).

The contact water conveyance ditches described in PE- 111578 were designed to transport non-contaminated contact water (*i.e.*, stormwater) to the East and West Sedimentation Ponds and will be constructed following completion of site preparation activities (*e.g.*, site grading, bedrock excavation) along the ditch lines. Until the ditches are operational, contact waters within the catchments are managed to remain on site using a system of berms, sumps, temporary ditches and baker tanks for intermediate storage and are then directed to the East WWTP for treatment, or the East and West Sedimentation Ponds prior to re-use or discharge.

The East and West WWTPs were commissioned to treat contaminated contact water in April and August 2024, respectively. The installed treatment capacities are 1,080 m³/day (East WWTP) and 120 m³/day (West WWTP). Lower than expected volumes of contaminated contact water have been encountered during construction; therefore, operation of the West WWTP has been suspended since September 25, 2024, and all contaminated contact waters are directed to the East WWTP for treatment. Treated effluent is generally directed to the East Sedimentation Pond. Occasionally the East WWTP effluent is discharged to Howe Sound at authorized discharge location SP-E-OUT.

Discharge from the East and West Sedimentation Ponds is controlled using pumps. Sedimentation pond effluent is pumped to the 2700GPM TSS settling system to remove TSS prior to discharge. Each sedimentation pond has an associated authorized discharge location (stations SP-E-OUT and SP-W-OUT) with an initial dilution zone (IDZ) where discharged water mixes with Howe Sound surface waters. The IDZ is defined in PE-111578 and extends in a 150 m radius from each point of discharge into Howe Sound. Since June 2025, surplus contact water in the East Sedimentation Pond is directed to the West Sedimentation Pond for storage or discharge, and discharge of clarified non-contaminated contact water to Howe Sound generally only occurs from the West Sedimentation Pond.

The flocculant-based 2700GPM TSS settling system has an installed capacity to clarify 14,700 m³/day of contact water and consists of six parallel treatment trains (Trains 1 to 6), each with an installed capacity of 2,450 m³/day. A staged commissioning of the 2700GPM system began June 2025 and was completed November 2025. Only one train is operated when contact water flows are low. Additional trains are activated as needed to match the influent volumes. Some of the TSS-clarified water may be recirculated back to the ponds or re-used for construction purposes (e.g., dust suppression).

The construction phase water management layout and monitoring stations are shown in Appendix A, Figure 1. Contact water collection and dewatering locations and photographs of the sedimentation ponds are shown in Appendix A, Figure 2 through Figure 5.

1.2 Weather and Water Management

Variable weather conditions were observed during the February 8 – 14 monitoring period, with precipitation recorded each day except on February 11. The total precipitation amount during the monitoring period was 41.0 mm. The daily weather conditions are summarized in Table 1.

Table 1:
Summary of Certified Project Area (CPA) Daily Weather Conditions.

Date	Precipitation (mm)	Max. Temp (°C)	Min. Temp (°C)	Weather Description
2026-02-08	0.6	10.1	3.8	Overcast
2026-02-09	16.2	6.6	3.9	Rain
2026-02-10	4.8	10.7	3.9	Rain
2026-02-11	0	10.0	2.8	Overcast
2026-02-12	0.6	7.6	3.2	Overcast
2026-02-13	12.0	6.6	4.2	Rain
2026-02-14	6.8	9.7	1.8	Rain

Note: Data retrieved from the Woodfibre on-site weather station operated by Stantec.

From February 8 – 14, the East Sedimentation Pond received water from the 6403 Sump, the MOF Sump and recirculated effluent from the East WWTP (Appendix A, Figure 2). A total of 1,338 m³ from the East Sedimentation Pond was transferred to the West Sedimentation Pond from February 8 – 14 (Appendix B, Table B-6).

Routine operation of the East WWTP continued during the monitoring period (February 8 – 14). Concrete contact water and water from the Wash Bay and Hydrovac Pit was periodically directed to the East WWTP for treatment, as well as water stored in the East Sedimentation Pond (Appendix A, Figure 2 and Figure 3). East WWTP treated effluent was discharged to the East Sedimentation Pond each day during the monitoring period (February 8 – 14). Daily water volumes processed by the East WWTP are provided in Appendix B (Table B-6).

From February 8 – 14, the West Sedimentation Pond received water from the Area 4100 and Area 4200 Sumps, the East Sedimentation Pond as well as recirculated effluent from the 2700GPM TSS settling system (Appendix A, Figure 3). West Sedimentation Pond effluent was clarified through the 2700GPM system each day during the monitoring period (February 8 – 14) and either recirculated back to the pond or intermittently discharged to Howe Sound. A total of 2,903 m³ of clarified effluent was intermittently discharged to Howe Sound from station SP-W-OUT on February 8, 9, 12 and 13. Clarified effluent was not reclaimed for construction use. Daily clarified effluent volumes from the 2700GPM TSS settling system recirculated to the West Sedimentation Pond or discharged to Howe Sound are provided in Appendix C (Table C-7).

2. Monitoring Summary

The locations of PE-111578 monitoring stations are shown on Figure 1. Monitoring is conducted by the on-site Environmental Monitors (Roe Environmental). Analytical samples are submitted by Roe Environmental to ALS Environmental in Burnaby, BC for testing.

The following PE-111578 and supplementary monitoring stations are currently being monitored:

- Non-contact diversion ditch outlet monitoring stations (OUT-01, OUT-02 and OUT-06).
- Creek water monitoring stations for Woodfibre, Mill and East Creek (SW-01, SW-02, SW-03, SW-04, SW-07).
- Contact water monitoring locations (SP-E-IN, WWTP-E-IN, COMB-WWTP-E-IN, WWTP-E-OUT, SP-W-IN, 2700GPM-IN, and 2700GPM-OUT).
- Supplementary contact water stations at the outlet of each sampling train. These samples are identified as W2700T#-OUT (with # equal to the train number).
- Effluent compliance stations (SP-E-OUT and SP-W-OUT). As described in Section 1.1, when there is surplus water, West Sedimentation Pond clarified effluent from the individual 2700GPM trains is directed to SP-W-OUT for discharge. From late September to early December 2025, SP-W-OUT was sampled from the discharge manhole. From December 1 to 8, a pipe manifold was installed that combines effluent from the individual trains into a single discharge line and is configured with a sampling port. Since December 8, samples have been collected at the sampling port or at the manhole.

- Howe Sound reference and IDZ monitoring stations (WQR1, WQR2, IDZ-E1, IDZ-E2, IDZ-W1, and IDZ-W2).

The diversion ditch outlet at Outfall 11(OUT-11) does not receive water and will not be monitored until it is operational.

The influent culverts for East and West Sedimentation Ponds are not operational and the associated influent stations defined in PE-111578 (SP-E-IN-1, SP-E-IN-2, SP-W-IN-1 and SP-W-IN-2) have been replaced with temporary influent monitoring stations SP-E-IN and SP-W-IN (East and West Sedimentation Pond, respectively) located in-pond, at the influent end of each pond.

A flocculant-based TSS settling system (2700GPM) is used at the West Sedimentation Pond as described in Section 1.1. Influent and effluent are monitored at stations 2700GPM-IN and 2700GPM-OUT, respectively. The 2700GPM-OUT station represents the combined discharge line from all six individual treatment trains when clarified effluent is directed to the West Sedimentation Pond and is equivalent to the SP-W-OUT station. At times when only one 2700GPM treatment train is operated, the 2700GPM-OUT sample may be collected at the outlet of that train. Monitoring of the individual 2700GPM settling system treatment trains is supplemental to the PE-111578 monitoring requirements and is conducted at the discretion of field staff.

Water quality was monitored at stations SW-01, SW-04, IDZ-E1, IDZ-E2, IDZ-W1, IDZ-W2, WQR1, WQR2, SP-E-IN, WWTP-E-IN, COMB-WWTP-E-IN, WWTP-E-OUT, SP-W-IN, SP-W-OUT, 2700GPM-IN, W2700T1-OUT, W2700T2-OUT, and W2700T4-OUT during the monitoring period (February 8 – 14). Sampling dates and parameters tested are summarized in Table 2.

Overall, the PE-111578 monitoring requirements that were applicable during the monitoring period (February 8 – 14) were met. The initial high frequency monitoring requirements outlined in effluent permit PE-111578 for the sedimentation ponds, WWTP and IDZ stations have been met. On June 25, 2025, BCER approved the implementation of low-frequency (*i.e.*, bi-monthly and monthly) monitoring requirements specified in PE-111578 for all parameters, except for metals, hexavalent chromium, and methylmercury, which continue to be monitored weekly at sedimentation pond and WWTP stations.

Daily field parameters and a weekly analytical sample were not collected at the east catchment effluent compliance station (SP-E-OUT) as there was no discharge to Howe Sound from the East Sedimentation Pond during the monitoring period (February 8 – 14). Daily field parameters were not collected at the west catchment compliance station (SP-W-OUT) on February 10, 11, 12 and 14 as there was no discharge to Howe Sound from the West Sedimentation Pond at the time of monitoring. Daily field parameters were not collected at the influent and effluent stations of the East WWTP (WWTP-E-IN and WWTP-E-OUT, respectively) on February 8 and 11 as the East WWTP was not operated at the time of monitoring. Daily field parameters and a weekly analytical

sample were not collected at the influent and effluent stations of the West WWTP (WWTP-W-IN and WWTP-W-OUT, respectively) as it was not operational during the monitoring period (February 8 – 14).

**Table 2:
Summary of PE-111578 Monitoring Samples Collected February 8 – 14.**

Sampling Date	Sample	Description	Parameters Tested	Monitoring Frequency		
February 8, 2026	SP-E-IN	East Sedimentation Pond influent monitored at cell 1 of the pond	Field Parameters.	D		
	SP-W-IN	West Sedimentation Pond influent monitored at cell 1 of the pond	Field Parameters.	D		
	SP-W-OUT	West Sedimentation Pond clarified effluent discharge to Howe Sound, collected at the manifold that combines effluent from the individual 2700GPM trains into a single discharge line configured with a SP-W-OUT sampling port				
	SW-01	Lower Reach of Woodfibre Creek (near the mouth)	Field, Physical & General Parameters, VH & BTEX, EPHs & PAHs, Total, Dissolved and Speciated Metals, VOCs, Methylmercury, Dioxins & Furans.	M		
	SW-04	Lower Reach of East Creek (near the outlet to the outfall culvert)				
February 9, 2026	SP-E-IN	East Sedimentation Pond influent monitored at cell 1 of the pond	Field Parameters.	D		
	WWTP-E-IN	East WWTP at the influent meter box	Field Parameters.	D		
	WWTP-E-OUT	East WWTP at the effluent meter box	Field, Physical & General Parameters, Total, Dissolved and Speciated Metals, Methylmercury and Acute Toxicity.	D, M ₂ , W, Q		
	SP-W-IN	West Sedimentation Pond influent monitored at cell 1 of the pond	Field, Physical & General Parameters, Total, Dissolved and Speciated Metals, and Methylmercury.	D, M ₂ , W		
	SP-W-OUT	West Sedimentation Pond clarified effluent discharge to Howe Sound, collected at the manifold that combines effluent from the individual 2700GPM trains into a single discharge line configured with a SP-W-OUT sampling port	Field, Physical & General Parameters, Total, Dissolved and Speciated Metals, Methylmercury and Acute Toxicity.	D, M ₂ , W, Q		
	2700GPM-IN	2700GPM TSS settling system at the influent meter box	Field, Physical & General Parameters, Total, Dissolved and Speciated Metals, and Methylmercury.	P		
	W2700T1-OUT	2700GPM TSS settling system at the outlet of Train 1	Field, Physical & General Parameters, Total, Dissolved and Speciated Metals, and Methylmercury.	P		
	W2700T2-OUT	2700GPM TSS settling system at the outlet of Train 2				
	W2700T4-OUT	2700GPM TSS settling system at the outlet of Train 4				
	IDZ-W1-0.5	Howe Sound IDZ station W1; 0.5 m below surface	Field, Physical & General Parameters, VH & BTEX, EPHs & PAHs, Total, Dissolved and Speciated Metals, VOCs, Methylmercury, Dioxins & Furans, Chronic Toxicity.	M, Q		
	IDZ-W1-2m	Howe Sound IDZ station W1; 2 m below surface				
	IDZ-W1-SF	Howe Sound IDZ station W1; 2 m above the seafloor				
	IDZ-W2-0.5	Howe Sound IDZ station W2; 0.5 m below surface				
	IDZ-W2-2m	Howe Sound IDZ station W2; 2 m below surface				
	IDZ-W2-SF	Howe Sound IDZ station W2; 2 m above the seafloor				
	WQR2-0.5	Reference site 2; 0.5 m below surface				
	WQR2-2m	Reference site 2; 2 m below surface				
	WQR2-SF	Reference site 2; 2 m above the seafloor				
	IDZ-E1-0.5	Howe Sound IDZ station E1; 0.5 m below surface				
	IDZ-E1-2m	Howe Sound IDZ station E1; 2 m below surface				
	IDZ-E1-SF	Howe Sound IDZ station E1; 2 m above the seafloor				
	IDZ-E2-0.5	Howe Sound IDZ station E2; 0.5 m below surface				
	IDZ-E2-2m	Howe Sound IDZ station E2; 2 m below surface				
	IDZ-E2-SF	Howe Sound IDZ station E2; 2 m above the seafloor				
	WQR1-0.5	Reference site 1; 0.5 m below surface				
	WQR1-2m	Reference site 1; 2 m below surface				
WQR1-SF	Reference site 1; 2 m above the seafloor					
February 10, 2026	SP-E-IN	East Sedimentation Pond influent monitored at cell 1 of the pond			Field Parameters.	D
	WWTP-E-IN	East WWTP at the influent meter box			Field Parameters.	D
	WWTP-E-OUT	East WWTP at the effluent meter box				
	SP-W-IN	West Sedimentation Pond influent monitored at cell 1 of the pond	Field Parameters.	D		
	SP-W-OUT	West Sedimentation Pond clarified effluent discharge to Howe Sound, collected at the manifold that combines effluent from the individual 2700GPM trains into a single discharge line configured with a SP-W-OUT sampling port	Field Parameters.	D		
2700GPM-IN	2700GPM TSS settling system at the influent meter box	Field Parameters.	P			
February 11, 2026	SP-E-IN	East Sedimentation Pond influent monitored at cell 1 of the pond	Field Parameters.	D		
	SP-W-IN	West Sedimentation Pond influent monitored at cell 1 of the pond	Field Parameters.	D		
	2700GPM-IN	2700GPM TSS settling system at the influent meter box	Field Parameters.	P		
	W2700T1-OUT	2700GPM TSS settling system at the outlet of Train 1	Field & Physical Parameters, Total, Dissolved and Speciated Metals	P		
	W2700T2-OUT	2700GPM TSS settling system at the outlet of Train 2				
	W2700T4-OUT	2700GPM TSS settling system at the outlet of Train 4				
February 12, 2026	SP-E-IN	East Sedimentation Pond influent monitored at cell 1 of the pond	Field, Physical & General Parameters, Total, Dissolved and Speciated Metals, and Methylmercury.	D, M ₂ , W		
	WWTP-E-IN	East WWTP at the influent meter box	Field, Physical & General Parameters, Total, Dissolved and Speciated Metals, and Methylmercury.	D, M ₂ , W		
	WWTP-E-OUT	East WWTP at the effluent meter box				
	COMB-WWTP-E-IN	Combined East WWTP influent from the concrete contact water treatment stream and the East Sedimentation Pond, collected from the heated frac tank	Field & Physical Parameters, Total, Dissolved and Speciated Metals, and Methylmercury.	P		
	SP-W-IN	West Sedimentation Pond influent monitored at cell 1 of the pond	Field Parameters.	D		
February 13, 2026	SP-E-IN	East Sedimentation Pond influent monitored at cell 1 of the pond	Field Parameters.	D		
	WWTP-E-IN	East WWTP at the influent meter box	Field Parameters.	D		
	WWTP-E-OUT	East WWTP at the effluent meter box				
	SP-W-IN	West Sedimentation Pond influent monitored at cell 1 of the pond	Field Parameters.	D		
	SP-W-OUT	West Sedimentation Pond clarified effluent discharge to Howe Sound, collected at the manifold that combines effluent from the individual 2700GPM trains into a single discharge line configured with a SP-W-OUT sampling port	Field Parameters.	D		
	2700GPM-IN	2700GPM TSS settling system at the influent meter box	Field Parameters.	D		

**Table 2 (continued):
Summary of PE-111578 Monitoring Samples Collected February 8 – 14.**

Sampling Date	Sample	Description	Parameters Tested	Monitoring Frequency
February 14, 2026	SP-E-IN	East Sedimentation Pond influent monitored at cell 1 of the pond	Field Parameters.	D
	WWTP-E-IN	East WWTP at the influent meter box	Field Parameters.	D
	WWTP-E-OUT	East WWTP at the effluent meter box	Field, Physical & General Parameters, Total, Dissolved and Speciated Metals.	D, M ₂ , P
	SP-W-IN	West Sedimentation Pond influent monitored at cell 1 of the pond	Field Parameters.	D
	2700GPM-IN	2700GPM TSS settling system at the influent meter box	Field Parameters.	P

Notes:

Monitoring frequency requirements under PE-111578 are indicated as follows:

D – daily monitoring of field parameters at WWTP and sedimentation pond influent and effluent stations.

M – monthly monitoring for all parameters at WWTP, sedimentation pond and receiving environment stations. Monthly monitoring for General parameters, except ammonia, nitrate and nitrite (*i.e.*, nitrogen species) are monitored weekly during blasting season.

M₂ – bi-monthly monitoring for physical parameters at WWTP and sedimentation pond stations.

W – weekly monitoring for metals, chromium speciation and methylmercury at WWTP and sedimentation pond influent and effluent stations, effective June 25, 2025.

P – periodic monitoring for targeted parameters that is supplementary to PE-111578 requirements.

Q – quarterly monitoring for toxicity.

3. Water Quality Results

3.1 Summary of Reported Results

Analytical results and associated field measurements included in this weekly report (Report #101) are listed below in Table 3, with additional field measurements presented in Table B-5 (Appendix B) and Table C-6 (Appendix C). Testing for methylmercury, dioxins, furans and toxicity may require four weeks or longer to complete. Analytical results not reported will be included in future weekly reports. Reporting of results is pending for the following samples and parameters:

- SW-01, SW-02, SW-03, SW-04 and SW-07 collected January 5 (dioxins and furans);
- SP-W-OUT and 2700GPM-IN collected January 11 (dioxins and furans);
- IDZ-W1, IDZ-W2 and WQR2 collected January 11 (dioxins and furans);
- SP-E-OUT collected January 12 (dioxins and furans);
- IDZ-E1, IDZ-E2 and WQR1 collected January 14 (dioxins and furans);
- SP-W-IN, 2700GPM-IN and SP-W-OUT collected February 1 (dioxins and furans);
- SP-E-IN, WWTP-E-IN and WWTP-E-OUT collected February 3 (dioxins and furans);
- SW-02, SW-03 and SW-07 collected February 7 (field and all analytical parameters);
- SW-01 and SW-04 collected February 8 (field and all analytical parameters);
- WWTP-E-OUT and SP-W-OUT collected February 9 (acute toxicity);
- IDZ-E1, IDZ-E2, IDZ-W1, IDZ-W2, WQR1 and WQR2 collected February 9 (field and all analytical parameters, chronic toxicity);
- SP-E-IN, WWTP-E-IN, COMB-WWTP-E-IN and WWTP-E-OUT collected February 12 (total mercury and methylmercury);
- WWTP-E-OUT collected February 14 (all analytical parameters).

**Table 3:
Summary of Analytical Results and Associated Field Measurements Included in Weekly Discharge and Compliance Report #101.**

Sample	Description	Sampling Date	Parameters Reported
SP-W-IN	West Sedimentation Pond influent monitored at cell 1 of the pond	January 4, 2026	Dioxins and Furans.
SP-W-OUT	West Sedimentation Pond clarified effluent discharge to Howe Sound, collected at the manifold that combines effluent from the individual 2700GPM trains into a single discharge line configured with a new SP-W-OUT sampling port		
2700GPM-IN	2700GPM TSS settling system at the influent meter box		
SP-E-IN	East Sedimentation Pond influent monitored at cell 1 of the pond	January 5, 2026	Dioxins and Furans.
WWTP-E-IN	East WWTP at the influent meter box		
WWTP-E-OUT	East WWTP at the effluent meter box		
SP-E-OUT	East WWTP treated effluent, collected at the sampling port	January 12, 2026	Dioxins and Furans.
OUT-01	Non-contact water diversion ditch outlet	February 2, 2026	Field, Physical and General Parameters, Total and Dissolved Metals, and Methylmercury.
OUT-02	Non-contact water diversion ditch outlet		
OUT-06	Non-contact water diversion ditch outlet		
SP-E-IN	East Sedimentation Pond influent monitored at cell 1 of the pond	February 3, 2026	Methylmercury.
WWTP-E-IN	East WWTP at the influent meter box		
WWTP-E-OUT	East WWTP at the effluent meter box		
COMB-WWTP-E-IN	Combined East WWTP influent from the concrete contact water treatment stream and the East Sedimentation Pond, collected from the heated frac tank		
SP-W-IN	West Sedimentation Pond influent monitored at cell 1 of the pond	February 9, 2026	Field, Physical and General Parameters, Total and Dissolved Metals, Hexavalent Chromium, and Methylmercury.
SP-W-OUT	West Sedimentation Pond clarified effluent discharge to Howe Sound, collected at the manifold that combines effluent from the individual 2700GPM trains into a single discharge line configured with a new SP-W-OUT sampling port		
2700GPM-IN	2700GPM TSS settling system at the influent meter box		
W2700T1-OUT	2700GPM TSS settling system at the outlet of Train 1		
W2700T2-OUT	2700GPM TSS settling system at the outlet of Train 2		
W2700T4-OUT	2700GPM TSS settling system at the outlet of Train 4		
WWTP-E-OUT	East WWTP at the effluent meter box	February 11, 2026	Field, Physical and General Parameters, Total and Dissolved Metals, and Hexavalent Chromium.
W2700T1-OUT	2700GPM TSS settling system at the outlet of Train 1		
W2700T2-OUT	2700GPM TSS settling system at the outlet of Train 2		
W2700T4-OUT	2700GPM TSS settling system at the outlet of Train 4		
SP-E-IN	East Sedimentation Pond influent monitored at cell 1 of the pond	February 12, 2026	Field, Physical and General Parameters, Total and Dissolved Metals, and Hexavalent Chromium.
WWTP-E-IN	East WWTP at the influent meter box		
WWTP-E-OUT	East WWTP at the effluent meter box		
COMB-WWTP-E-IN	Combined East WWTP influent from the concrete contact water treatment stream and the East Sedimentation Pond, collected from the heated frac tank		Field and Physical Parameters, Total and Dissolved Metals, and Hexavalent Chromium.

3.2 Screening and Reporting Overview

Water quality and flow monitoring results are screened against operational minimum discharge objectives (MDOs) for the East WWTP, and PE-111578 discharge limits for sedimentation pond and 2700GPM TSS settling system stations. The East WWTP MDOs were set equal to Canadian Council of Ministers of the Environment (CCME) water quality guidelines (WQGs) and the PE-111578 discharge limits. Contact and non-contact water monitoring results are also screened against Canadian (Canadian Council of Ministers of the Environment, CCME), Federal (Environment and Climate Change Canada, ECCC) and BC water quality guidelines (WQGs). All water quality data are recorded in the Woodfibre LNG environmental monitoring database. However, for brevity, a sub-set of the results are presented in the weekly report appendices. Results are reported for parameters with a freshwater, estuarine or marine water quality guideline for the protection of aquatic life, parameters with a discharge limit, parameters of potential concern (*i.e.*, dioxins and furans) as well as other parameters that are relevant for water quality interpretation.

It is expected that samples of contact water and samples collected within the IDZ (*i.e.*, mixing zone) defined in PE-111578 for the authorized discharge locations may have parameter concentrations above baseline or background (*i.e.*, reference station) concentrations due to project influence. As well, for receiving environment samples, parameter concentrations above a WQG value but within the range of values observed in the baseline monitoring program are considered to represent the background conditions of the water.

The values used for screening are listed in the water quality tables provided in the appendices. Results above a screening value are highlighted in the tables. Samples collected from sedimentation pond effluent that is discharged to Howe Sound (monitored at stations SP-E-OUT and SP-W-OUT) are evaluated for non-compliance to PE-111578 discharge limits. Exceedances in contact water that remains on-site and is not discharged (e.g., WWTP influent and effluent, sedimentation pond influent, TSS settling system influent, and TSS settling system effluent that is recirculated) are screened for comparison purposes only, and exceedances in these samples do not represent non-compliance to the PE-111578 conditions.

Canadian, Federal and BC WQGs are not specified for dioxins and furans. The general term “dioxins and furans” refers to a total of 210 polychlorinated dibenzo-*p*-dioxin (PCDD) and polychlorinated dibenzofuran (PCDF) compounds. A sub-set of 17 of the most toxic PCDDs and PCDFs are typically evaluated for toxicity by converting the individual parameter concentrations to toxic equivalent (TEQ) values that are summed and evaluated as a single PCDD/F TEQ parameter. To address uncertainties for results reported as not detected, two PCDD/F TEQ values are reported. A “lower-bound PCDD/F TEQ” is calculated assuming a concentration of zero for results reported as not detected, therefore, if all 17 of the individual compounds in the sub-set are

not detected the lower-bound PCDD/F TEQ will equal zero. An “upper-bound PCDD/F TEQ” is calculated assuming a concentration equal to the detection limit for results reported as not detected. These two parameters span the range of possible TEQs if one or more of the PCDDs and PCDFs are reported as not detected.

The BC WQG for total mercury is a sample-specific calculated value that is based on the concentration of methylmercury in a sample. Although an approved BC WQG for the protection of aquatic life for methylmercury has not been explicitly established, the BC Ambient Water Quality Guidelines for Mercury Overview Report indicates the total mercury WQG is derived from a methylmercury concentration threshold of 0.0001 µg/L (0.1 ng/L) that is set at a concentration that protects fish from mercury bioaccumulation to levels that could harm wildlife that consumes fish. Therefore, if methylmercury results are reported, the 0.0001 µg/L value is presented as a WQG to support the interpretation of methylmercury results.

A summary of reported and pending results is provided in Section 3.1. Results for effluents from East WWTP, 2700GPM TSS settling system, and East and West Sedimentation Ponds are discussed in Section 3.3 and Section 3.4. The water quality monitored at non-contact water diversion ditch outlets and in the receiving environment is described in Section 3.5 to Section 3.7. Sediment samples are collected annually at stations IDZ-E-SED and IDZ-W-SED and are discussed in Section 3.7 when they are reported. Sediment samples were last collected July 2025 and the analytical results were presented in Report #82.

3.3 East Catchment

The east catchment water quality and flow monitoring results for stations at the East WWTP, the East Sedimentation Pond, and the authorized discharge location (SP-E-OUT) are discussed in this section and are tabulated in Appendix B.

Results are presented for field measurements of influent quality for the East Sedimentation Pond and East WWTP influent and effluent quality collected February 8 – 14 , as well as analytical results for samples collected February 9 (station WWTP-E-OUT) and February 12 (stations SP-E-IN, WWTP-E-IN, COMB-WWTP-E-IN and WWTP-E-OUT). Field measurements for the East WWTP effluent samples (WWTP-E-OUT) collected February 8 – 14 and the analytical samples collected February 9 and 12 met MDOs except for total copper and hexavalent chromium on February 12 (Appendix B, Table B-1). Follow-up actions for total copper and hexavalent chromium are tracked in Table 5.

East WWTP effluent was directed to the East Sedimentation Pond and there was no discharge from the pond to Howe Sound from February 8 – 14 (Section 1.2; Table B-6 of Appendix B). Therefore, water quality samples and field measurements were not collected at the SP-E-OUT discharge location.

Dioxins and furans results were available at the time of reporting for East Sedimentation Pond influent and East WWTP influent and effluent collected January 5 (as discussed in Report #96) as well as East WWTP effluent that was discharged to Howe Sound from SP-E-OUT on January 12 (as discussed in Report #97). Results are presented in Appendix B, Table B-4.

3.4 West Catchment

The west catchment water quality monitoring results for stations at the West Sedimentation Pond, the 2700GPM TSS settling system, and the authorized discharge location (SP-W-OUT) are discussed in this section and are tabulated in Appendix C. Operation of the West WWTP is suspended (refer to Section 1.1) and monitoring results are therefore not available for the stations at this facility.

As discussed in Section 1.2, a total of 2,903 m³ of clarified sedimentation pond effluent from the 2700GPM TSS Settling System was intermittently discharged to Howe Sound from SP-W-OUT on February 8, 9, 12 and 13.

Results are presented for field measurements of influent and effluent quality for the West Sedimentation Pond and the 2700GPM TSS settling system collected February 8 – 14, as well as analytical samples collected February 9 (stations SP-W-IN, SP-W-OUT, 2700GPM-IN, W2700T1-OUT, W2700T2-OUT and W2700T4-OUT) and February 11 (stations W2700T1-OUT, W2700T2-OUT and W2700T4-OUT). Field measurements collected February 8 – 14 and the analytical samples collected at SP-W-OUT on February 9 met PE-111578 discharge limits and WQGs except for total copper (Table 4; Appendix C, Table C-3, C-4 and C-6).

**Table 4:
Summary of Parameters Exceeding PE-111578 Discharge Limits in Effluent Discharged from SP-W-OUT for Field and Analytical Results Available at the Time of Reporting**

Parameter	Units	Discharge Limit	N	N >Limit	Commentary
Total Copper	mg/L	0.0043	2	2	Total copper measured in duplicate samples collected at station SP-W-OUT on February 9 (0.00799 and 0.00466 mg/L) were 1.9 and 1.1 times greater than the PE-111578 discharge limit, respectively. BCER has been notified.

N = number of samples.

Dioxins and furans results were available at the time of reporting for West Sedimentation Pond and 2700GPM TSS settling system influent as well as clarified sedimentation pond effluent from the 2700GPM TSS settling system that was discharged to Howe Sound from SP-W-OUT on January 4 (as discussed in Report #96). Results are presented in Appendix C, Table C-5.

3.5 Non-Contact Water Diversion Ditch Outlets

Analytical results were available at the time of reporting for the non-contact water diversion ditch outlet samples collected at stations OUT-01, OUT-02 and OUT-06 on February 2 (as discussed in Report #100). The analytical results, field parameters, and WQGs are summarized in Appendix D.

Parameter concentrations met WQGs except total aluminum and dissolved copper in the sample collected at OUT-06 on February 2. Total aluminum (0.230 mg/L) and dissolved copper (0.00079 mg/L) were above the long-term WQGs. The total aluminum and dissolved copper concentrations measured at OUT-06 are within the range of values observed during the pre-construction baseline monitoring of diversion ditch water quality (0.118 to 0.433 mg/L for total aluminum and 0.00052 to 0.00095 mg/L for dissolved copper).

For all samples, methylmercury concentrations ranged from <0.000020 to 0.000028 µg/L and met the WQG. The corresponding total mercury results met WQGs. Results are tabulated in Appendix D, Table D-2.

3.6 Freshwater and Estuarine Water Receiving Environment

Analytical results for freshwater and estuarine water samples were not available at the time of reporting.

3.7 Marine Water Receiving Environment

Analytical results for marine water samples were not available at the time of reporting.

3.8 Quality Control

This section presents the results of the quality control (QC) evaluation for the PE-111578 weekly report (Table 5). The evaluation includes a review of field and lab QC, completeness of the weekly report (*e.g.*, pending data), completeness of the monitoring program, confirmation of recordkeeping, evaluation of compliance and review of water management activities. Items flagged for follow-up in Section 3 are also tracked in Table 5. Any items flagged for follow-up are carried forward to future reports until they are closed.

**Table 5:
Weekly Report QC Evaluations and Ongoing Items**

QC Procedure	Observation	Investigation/Resolution
Reporting Period (February 8 – 14, Report #101)		
Authorized Works and Monitoring Program Evaluation	The authorized works and monitoring stations have not been established as described in PE-111578.	The PE-111578 authorized works for water management have been constructed, except for some of the conveyance ditches, which require completion of site grading prior to installation. Sumps, pumps and hoses are used for temporary conveyance until the ditches are completed. The lower reach of East Creek was temporarily diverted through Outfall 11 from September 17, 2024 to November 18, 2025. As November 19, 2025, East Creek flows have been returned to the lower Channel that discharges to Howe Sound through the Outfall 12 culverts (OUT-12). The culvert at OUT-01 is being replaced and diversion water flows to OUT-01 have been redirected to OUT-02. Outfall 11 (OUT-11) has been constructed but is not in use. All monitoring stations have been established except at SP-E-IN-1, SP-E-IN-2, SP-W-IN-1 and SP- W- IN- 2 where substitute stations are established in lieu of those listed in PE-111578 (refer to Section 2). This item remains open.
Report #101: Non-compliant Discharge	Total copper above the discharge limit.	Total copper concentrations measured in duplicate samples collected at station SP-W-OUT on February 9 (0.00799 and 0.00466 mg/L) were 1.9 and 1.1 times greater than the PE-111578 discharge limit, respectively. BCER has been notified. A root cause investigation is underway. This item remains open.
Report #101: WWTP Performance Evaluation	Total copper above the MDO.	The total copper concentration was 0.00443 mg/L in the sample collected at WWTP-E-OUT on February 12 and was above the MDO (0.0043 mg/L). The WWTP treatment performance for total copper will continue to be evaluated through the end of February 2026 to determine if this is an isolated event or a recurring issue that requires additional investigation. This item remains open.
Report #101: Pending Data	Analytical results not reported.	Field parameters and analytical results for receiving environment and treated water samples collected February 9 and 14, respectively, as well as acute toxicity results for treated water samples collected February 9 and total mercury and methylmercury results for contact and treated water samples collected February 12 are pending and will be included in future weekly reports when available. This item remains open.
Ongoing Items from Previous Weekly Reports		
Report #96: Pending Data	Analytical results not reported.	Previously pending dioxins and furans results for contact and treated water samples collected January 4 and 5 are included in Report #101. Dioxins and furans results for receiving environment samples collected January 5 are pending and will be included in future weekly reports when available. This item remains open.
Report #97: Pending Data	Analytical results not reported.	Previously pending dioxins and furans results for the treated water sample collected January 12 is included in Report #101. Dioxins and furans results for receiving environment samples collected January 11 and 14 and contact and treated water samples collected January 11 are pending and will be included in future weekly reports when available. This item remains open.
Report #98: WWTP Performance Evaluation	Hexavalent chromium above the MDO.	This item was first noted in Report #98. The hexavalent chromium concentrations were 0.00154, 0.00153 and 0.00224 mg/L in the samples collected at WWTP-E-OUT on January 20, 28 and February 12, respectively, and were above the MDO (0.0015 mg/L). However, hexavalent chromium met the MDO in samples collected at WWTP-E-OUT on February 3 and 9 (0.00081 and 0.00138 mg/L, respectively). The WWTP treatment performance for hexavalent chromium will continue to be evaluated through the end of February 2026 to determine if this is an isolated event or a recurring issue that requires additional investigation. This item remains open.
Report #100: Pending Data	Analytical results not reported.	Previously pending field parameters and analytical results for non-contact water diversion ditch outlet samples collected February 2 and total mercury and methylmercury results for contact and treated water samples collected February 3 are included in Report #101. Field parameters and analytical results for receiving environment samples collected February 7 as well as dioxins and furans results for contact and treated water samples collected February 1 and 3 are pending and will be included in future weekly reports when available. This item remains open.

Notes:

Result QA/QC screening includes the evaluation of field and lab QC results, comparison of total and dissolved metal results and review for modified detection limits.

Pending data are outstanding results from monitoring samples reported in the current or previous weekly reports.

Authorized works and monitoring program evaluation is an assessment of the completeness of the authorized works and monitoring program compared to PE-111578 specified or implied requirements.

WWTP performance evaluation is an assessment of WWTP effluent quality compared to operational MDOs.

Data QC indicates an evaluation of data trends or inter-parameter relationships that suggest a test result may not be representative of water quality at the time of monitoring.

Non-compliant discharge indicates exceedance of a discharge limit or a discharge that bypasses the sedimentation pond discharge location.

Potential project influence is an assessment that water quality at creek and Howe Sound baseline stations are above the baseline concentration range and may indicate project influence at these stations.

4. Closure


This weekly report is a desktop review by Lorax of the PE-111578 discharge and compliance monitoring program records, reports and results provided by Woodfibre LNG and prime contractor McDermott International and their sub-contractors. The records reviewed and analyzed by Lorax include ALS Environmental laboratory test reports and site reports (from Roe Environmental, LB LNG, McDermott and Woodfibre LNG). Verbal or electronic communications between Lorax, and Roe Environmental, LB LNG, McDermott, and Woodfibre LNG staff are conducted as needed to confirm the information presented in this report.

Regards,

LORAX ENVIRONMENTAL SERVICES LTD.



Holly Pelletier, B.Sc., GIT.
Environmental Geoscientist



Cheng Kuang, M.Sc., RPBio.
Environmental Scientist

***Appendix A:
Figures and Site Images***



World Imagery: District of Squamish. Additional imagery provided by McDermott International captured February 2nd, 2026.

LEGEND	
	Freshwater Monitoring Station
	Marine Water Monitoring Station
	Clean Water Diversion Discharge Station
	Sedimentation Pond Monitoring Stations (Water Quality)
	Wastewater Treatment Plant (WWTP)
	Certified Project Area
	Watercourse
	Non-Contact Ditch
	Culvert / Outfall / Pipeline
	Non-Contact Water Transfer Hose
	Bathymetry Contour (Major: 50m)
	Bathymetry Contour (Minor: 10m)

DATE SAVED:	Feb 20, 2026
DRAWN BY:	DM
REVIEWED:	PM
VERSION:	1

Coordinate System: NAD 1983 UTM Zone 10N
 Projection: Transverse Mercator
 Datum: North American 1983
 Units: Metre
1:6,000

CLIENT:

PROJECT: **Woodfibre LNG Project Construction Phase**

TITLE: Site Layout and Water Quality Monitoring Stations for PE-111578 (February 14, 2026)

PROJECT #: A825-1

FIGURE: 1




Figure 2: East Catchment contact water management facilities (February 8 – 14).



Figure 3: West Catchment contact water management facilities (February 8 – 14).



Figure 4: Aerial view of the East Sedimentation Pond (February 12, 2026). The East WWTP is located on the left side of the pond.




Figure 5: Aerial view of the West Sedimentation Pond (February 12, 2026).

***Appendix B:
East Catchment Monitoring Results***

**Table B-1:
East WWTP Influent and Effluent Analytical Results Received at the Time of Reporting.**

Parameter	Unit	Lowest Applicable Guideline ¹		PE-111578 Discharge Limit	Station WWTP-E-IN	Station COMB-WWTP-E-IN	Station WWTP-E-OUT	Station WWTP-E-OUT
					Influent	Influent	Effluent	Effluent
		WWTP-E-IN	COMB-WWTP-E-IN		WWTP-E-OUT	WWTP-E-OUT		
		VA26A3466-002	VA26A3466-006		VA26A3106-009	VA26A3466-003		
				2026-02-12 9:23	2026-02-12 10:35	2026-02-09 8:31	2026-02-12 15:11	
General Parameters								
pH - Field	pH units	- ²	-	5.5 - 9.0	7.1	8.0	6.2	6.4
Specific Conductivity - Field	µS/cm	-	-	-	577	-	663	576
Temperature - Field	°C	-	-	-	8.0	-	7.9	8.2
Salinity - Field	ppt	-	-	-	0.28	-	0.32	0.28
Turbidity - Field	NTU	-	-	-	29.59	-	9.18	2.92
TSS	mg/L	-	-	25 or 75 ⁶	18	122	<3.0	<3.0
Dissolved Oxygen - Field	mg/L	≥8	-	-	11.21	-	11.39	12.23
Total Hardness	mg/L	-	-	-	83.5	138	18.7	33.4
Dissolved Hardness	mg/L	-	-	-	80.4	107	18	33.3
Anions and Nutrients								
Sulphate	mg/L	-	-	-	157	-	228	212
Chloride	mg/L	-	-	-	4.46	-	3.81	4.57
Fluoride	mg/L	-	1.5	-	0.113	-	0.085	<0.100
Ammonia (N-NH ₃)	mg/L	2.9-29 ³	19-191 ³	-	<0.0050	-	0.0471	0.0314
Nitrite (N-NO ₂)	mg/L	-	-	-	0.0073	-	0.005	0.0077
Nitrate (N-NO ₃)	mg/L	3.7	339	-	0.258	-	0.178	0.275
Total Organic Carbon (TOC)	mg/L	-	-	-	2.33	-	1.88	2.03
Dissolved Organic Carbon (DOC)	mg/L	-	-	-	2.27	-	2.04	1.93
Total Metals								
Aluminum, total (T-Al)	mg/L	-	-	-	1.00	8.3	0.471	0.0599
Antimony, total (T-Sb)	mg/L	-	0.27 ⁴	-	0.00079	0.00119	0.0007	0.00083
Arsenic, total (T-As)	mg/L	0.0125	-	-	0.00181	0.0043	0.00086	0.00123
Barium, total (T-Ba)	mg/L	-	-	-	0.0215	0.131	0.00477	0.00328
Beryllium, total (T-Be)	mg/L	0.1	-	-	0.00002	0.00019	<0.000020	<0.000020
Boron, total (T-B)	mg/L	1.2	-	-	0.034	0.043	0.025	0.032
Cadmium, total (T-Cd)	mg/L	0.00012	-	-	<0.0000350	0.000119	<0.0000200	<0.0000300
Chromium, total (T-Cr)	mg/L	-	-	-	0.00316	0.0116	0.0023	0.00218
Cobalt, total (T-Co)	mg/L	-	-	-	0.00033	0.00288	0.00011	<0.00010
Copper, total (T-Cu)	mg/L	- ²	- ²	0.0043	0.00311	0.0237	0.00144	0.00443
Iron, total (T-Fe)	mg/L	-	-	-	0.671	7.81	0.218	0.019
Lead, total (T-Pb)	mg/L	- ²	- ²	0.0035	0.000672	0.00747	0.000295	0.000175
Manganese, total (T-Mn)	mg/L	-	-	-	0.0425	0.237	0.00973	0.00407
Molybdenum, total (T-Mo)	mg/L	-	-	-	0.0500	0.0635	0.0522	0.0578
Nickel, total (T-Ni)	mg/L	0.0083	-	-	0.00066	0.00399	<0.00050	0.0049
Selenium, total (T-Se)	mg/L	0.002	-	-	0.000213	0.000384	0.000298	0.000267
Silver, total (T-Ag)	mg/L	0.0005	0.0037	-	<0.000010	0.000029	<0.000010	<0.000010
Thallium, total (T-Tl)	mg/L	-	-	-	<0.000010	0.000041	<0.000010	<0.000010
Uranium, total (T-U)	mg/L	-	-	-	0.00958	0.00931	0.00243	0.00743
Vanadium, total (T-V)	mg/L	- ²	-	0.0081	0.00405	0.0165	0.0026	0.00326
Zinc, total (T-Zn)	mg/L	- ²	- ²	0.0133	0.0085	0.0567	0.0036	0.0106
Hexavalent Chromium, total	mg/L	0.0015	-	-	0.00258	0.00232	0.00138	0.00224
Dissolved Metals								
Cadmium, dissolved (D-Cd)	mg/L	-	-	-	<0.0000200	<0.0000150	<0.0000200	<0.0000200
Copper, dissolved (D-Cu)	mg/L	-	-	-	0.00173	0.00197	0.00105	0.00177
Iron, dissolved (D-Fe)	mg/L	-	-	-	<0.010	0.018	0.013	0.011
Lead, dissolved (D-Pb)	mg/L	-	-	-	<0.000050	<0.000050	<0.000050	0.000054
Manganese, dissolved (D-Mn)	mg/L	-	-	-	0.0213	0.00346	0.00336	0.00358
Nickel, dissolved (D-Ni)	mg/L	-	-	-	<0.00050	<0.00050	<0.00050	<0.00050
Strontium, dissolved (D-Sr)	mg/L	-	-	-	0.165	0.236	0.066	0.112
Vanadium, dissolved (D-V)	mg/L	-	-	-	0.00276	0.00401	0.00204	0.00324
Zinc, dissolved (D-Zn)	mg/L	-	-	-	0.0027	<0.0010	0.002	0.0028
Polycyclic Aromatic Hydrocarbons (PAHs)								
Acenaphthene	mg/L	0.006	-	-	-	-	-	-
Acridine	mg/L	-	-	-	-	-	-	-
Anthracene	mg/L	-	-	-	-	-	-	-
Benz(a)anthracene	mg/L	-	-	-	-	-	-	-
Benzo(a)pyrene	mg/L	0.00001	-	-	-	-	-	-
Chrysene	mg/L	0.0001	-	-	-	-	-	-
Fluoranthene	mg/L	-	-	-	-	-	-	-
Fluorene	mg/L	0.012	-	-	-	-	-	-
1-methylnaphthalene	mg/L	0.001	-	-	-	-	-	-
2-methylnaphthalene	mg/L	0.001	-	-	-	-	-	-
Naphthalene	mg/L	0.001	-	-	-	-	-	-
Phenanthrene	mg/L	-	-	-	-	-	-	-
Pyrene	mg/L	-	-	-	-	-	-	-
Quinoline	mg/L	-	-	-	-	-	-	-
Volatile Organic Compounds (VOCs)								
Benzene	mg/L	0.11	-	-	-	-	-	-
Ethylbenzene	mg/L	0.25	-	-	-	-	-	-
Methyl-tert-butyl-ether	mg/L	5	0.44	-	-	-	-	-
Styrene	mg/L	-	-	-	-	-	-	-
Toluene	mg/L	0.215	-	-	-	-	-	-
Total Xylenes	mg/L	-	-	-	-	-	-	-
Chlorobenzene	mg/L	0.025	-	-	-	-	-	-
1,2-Dichlorobenzene	mg/L	0.042	-	-	-	-	-	-

Notes:

East catchment influents and East WWTP effluent were not discharged to Howe Sound. Results above screening values are only highlighted for comparative purposes.

Non-detect results are screened using the detection limit value.

Results **underlined in bold italics** exceed the applicable long-term water quality guideline for the protection of marine water aquatic life.

Shaded results exceed the applicable short-term water quality guideline for the protection of marine water aquatic life.

Results in **orange text** exceed the PE-111578 East Sedimentation Pond Discharge Limit.

The East Catchment did not discharge during the monitoring period (February 8 – 14).

¹ The lowest applicable guidelines from approved or working BC WQGs, Canadian (CCME) WQGs and Federal WQGs for marine waters.

² The WQG was not evaluated for parameters with discharge limits.

³ The BC WQG for total ammonia is salinity, pH and temperature dependent; see Tables 27E and 27F in BC WQG guidance document.

⁴ The working BC WQG for trivalent antimony [SB(III)] is 0.27 mg/L and is applied to total antimony results.

⁵ When MeHg ≤ 0.5% of total Hg, the BC WQG = 0.00002 mg/L. The Canadian WQG = 0.000016 mg/L.

⁶ The PE-111578 discharge limit for TSS is 25 mg/L under dry conditions and 75 mg/L for each day of Wet Conditions and for one day following the end of Wet Conditions.

**Table B-2:
East Sedimentation Pond Influent and Effluent Analytical Results Received at the Time of Reporting.**

Parameter	Unit	Lowest Applicable Guideline ¹		PE-111578 Discharge Limit	Station SP-E-IN
		Long Term	Short Term		Influent
					VA26A3466-001 2026-02-12 12:51
General Parameters					
pH - Field	pH units	- ²	-	5.5 - 9.0	8.4
Specific Conductivity - Field	µS/cm	-	-	-	608
Temperature - Field	°C	-	-	-	7.6
Salinity - Field	ppt	-	-	-	0.3
Turbidity - Field	NTU	-	-	-	18.54
TSS	mg/L	-	-	25 or 75 ⁶	15.6
Dissolved Oxygen - Field	mg/L	≥8	-	-	11.75
Total Hardness	mg/L	-	-	-	75.9
Dissolved Hardness	mg/L	-	-	-	70
Anions and Nutrients					
Sulphate	mg/L	-	-	-	162
Chloride	mg/L	-	-	-	4.53
Fluoride	mg/L	-	1.5	-	0.123
Ammonia (N-NH ₃)	mg/L	1.2 ³	7.9 ³	-	0.0111
Nitrite (N-NO ₂)	mg/L	-	-	-	0.007
Nitrate (N-NO ₃)	mg/L	3.7	339	-	0.292
Total Organic Carbon (TOC)	mg/L	-	-	-	2.92
Dissolved Organic Carbon (DOC)	mg/L	-	-	-	2.4
Total Metals					
Aluminum, total (T-Al)	mg/L	-	-	-	0.784
Antimony, total (T-Sb)	mg/L	-	0.27 ⁴	-	0.0008
Arsenic, total (T-As)	mg/L	0.0125	-	-	0.00188
Barium, total (T-Ba)	mg/L	-	-	-	0.0187
Beryllium, total (T-Be)	mg/L	0.1	-	-	<0.000020
Boron, total (T-B)	mg/L	1.2	-	-	0.031
Cadmium, total (T-Cd)	mg/L	0.00012	-	-	<0.0000350
Chromium, total (T-Cr)	mg/L	-	-	-	0.00529
Cobalt, total (T-Co)	mg/L	-	-	-	0.00028
Copper, total (T-Cu)	mg/L	- ²	- ²	0.0043	0.0032
Iron, total (T-Fe)	mg/L	-	-	-	0.593
Lead, total (T-Pb)	mg/L	- ²	- ²	0.0035	0.000723
Manganese, total (T-Mn)	mg/L	-	-	-	0.0309
Molybdenum, total (T-Mo)	mg/L	-	-	-	0.0631
Nickel, total (T-Ni)	mg/L	0.0083	-	-	<0.00050
Selenium, total (T-Se)	mg/L	0.002	-	-	0.000255
Silver, total (T-Ag)	mg/L	0.0005	0.0037	-	<0.000010
Thallium, total (T-Tl)	mg/L	-	-	-	<0.000010
Uranium, total (T-U)	mg/L	-	-	-	0.0105
Vanadium, total (T-V)	mg/L	- ²	-	0.0081	0.004
Zinc, total (T-Zn)	mg/L	- ²	- ²	0.0133	0.0062
Hexavalent Chromium, total	mg/L	0.0015	-	-	0.00406
Dissolved Metals					
Cadmium, dissolved (D-Cd)	mg/L	-	-	-	<0.0000250
Copper, dissolved (D-Cu)	mg/L	-	-	-	0.0018
Iron, dissolved (D-Fe)	mg/L	-	-	-	<0.010
Lead, dissolved (D-Pb)	mg/L	-	-	-	<0.000050
Manganese, dissolved (D-Mn)	mg/L	-	-	-	0.0132
Nickel, dissolved (D-Ni)	mg/L	-	-	-	<0.00050
Strontium, dissolved (D-Sr)	mg/L	-	-	-	0.167
Vanadium, dissolved (D-V)	mg/L	-	-	-	0.00292
Zinc, dissolved (D-Zn)	mg/L	-	-	-	0.0012
Polycyclic Aromatic Hydrocarbons (PAHs)					
Acenaphthene	mg/L	0.006	-	-	-
Acridine	mg/L	-	-	-	-
Anthracene	mg/L	-	-	-	-
Benz(a)anthracene	mg/L	-	-	-	-
Benzo(a)pyrene	mg/L	0.00001	-	-	-
Chrysene	mg/L	0.0001	-	-	-
Fluoranthene	mg/L	-	-	-	-
Fluorene	mg/L	0.012	-	-	-
1-methylnaphthalene	mg/L	0.001	-	-	-
2-methylnaphthalene	mg/L	0.001	-	-	-
Naphthalene	mg/L	0.001	-	-	-
Phenanthrene	mg/L	-	-	-	-
Pyrene	mg/L	-	-	-	-
Quinoline	mg/L	-	-	-	-
Volatile Organic Compounds (VOCs)					
Benzene	mg/L	0.11	-	-	-
Ethylbenzene	mg/L	0.25	-	-	-
Methyl-tert-butyl-ether	mg/L	5	0.44	-	-
Styrene	mg/L	-	-	-	-
Toluene	mg/L	0.215	-	-	-
Total Xylenes	mg/L	-	-	-	-
Chlorobenzene	mg/L	0.025	-	-	-
1,2-Dichlorobenzene	mg/L	0.042	-	-	-

Notes:

East catchment influents and East WWTP effluent were not discharged to Howe Sound. Results above screening values are only highlighted for comparative purposes. Non-detect results are screened using the detection limit value.

Results **underlined in bold italics** exceed the applicable long-term water quality guideline for the protection of marine water aquatic life.

Shaded results exceed the applicable short-term water quality guideline for the protection of marine water aquatic life.

Results in **orange text** exceeded the PE-111578 East Sedimentation Pond Discharge Limit.

The East Catchment did not discharge during the monitoring period (February 8 – 14).

¹ The lowest applicable guidelines from approved or working BC WQGs, Canadian (CCME) WQGs and Federal WQGs for marine waters.

² The WQG was not evaluated for parameters with discharge limits.

³ The BC WQG for total ammonia is salinity, pH and temperature dependent; see Tables 27E and 27F in BC WQG guidance document.

⁴ The working BC WQG for trivalent antimony [SB(III)] is 0.27 mg/L and is applied to total antimony results.

⁵ When MeHg ≤ 0.5% of total Hg, the BC WQG = 0.00002 mg/L. The Canadian WQG = 0.000016 mg/L.

⁶ The PE-111578 discharge limit for TSS is 25 mg/L under dry conditions and 75 mg/L for each day of Wet Conditions and for one day following the end of Wet Conditions.

**Table B-3:
East Catchment Methylmercury and Corresponding Total Mercury Results Received at the Time of Reporting.**

Parameter					Total Methylmercury	Total Mercury
Unit					µg/L	µg/L
Lowest Applicable Guideline ¹					0.0001 ²	0.0078-0.016 ^{3,4}
Station	Water Type	Sample ID	Lab ID	Sampling Date		
Influent						
SP-E-IN	Influent	SP-E-IN	VA26A2566-001	2026-02-03	0.000031	0.00356
WWTP-E-IN	Influent	WWTP-E-IN	VA26A2566-002	2026-02-03	0.000089	0.00692
COMB-WWTP-E-IN	Influent	COMB-WWTP-E-IN	VA26A2566-005	2026-02-03	<u>0.000211</u>	<u>0.178</u>
Effluent						
WWTP-E-OUT	Effluent	WWTP-E-OUT	VA26A2566-008	2026-02-03	0.000028	0.00284
WWTP-E-OUT	Effluent	WWTP-E-OUT	VA26A3106-009	2026-02-09	0.000092	0.00739

Notes:

East catchment influents and effluent were not discharged to Howe Sound. Results above screening values are only highlighted for comparative purposes. Non-detect results are screened using the detection limit value.

Results **underlined in bold italics** exceed the applicable long-term water quality guideline for the protection of marine aquatic life.

¹ The lowest applicable guidelines from approved or working BC WQGs, Canadian (CCME) WQGs and Federal WQGs.

² From BC Ambient Water Quality Guidelines for Mercury Overview Report. The methylmercury concentration threshold of 0.0001 µg/L (0.1 ng/L) is indicated as a WQG for the protection of wildlife and is set at a concentration that protects fish from mercury bioaccumulation to a level that may harm wildlife that consume fish.

³ CCME guideline for total mercury = 0.016 µg/L.

⁴ When MeHg ≤ 0.5% of total Hg, BC WQG = 0.02 µg/L. When MeHg > 0.5% of total Hg, BC WQG = 0.0001/(MeHg/Total Hg). Detection limit values are used to calculate the WQG for result reported as not detected.

**Table B-4:
East Catchment Dioxin and Furan Toxicity Equivalency Quantity (TEQ) Results Received at the Time of Reporting.**

Parameter					Lower Bound PCDD/F TEQ	Upper Bound PCDD/F TEQ
Unit					pg/L	pg/L
Station	Water Type	Sample ID	Lab ID	Sampling Date		
Influent						
SP-E-IN	Influent	SP-E-IN	VA26A0124-001	2026-01-05	0.085	2.01
WWTP-E-IN	Influent	WWTP-E-IN	VA26A0124-002	2026-01-05	2.80	6.00
Effluent						
SP-E-OUT	Effluent	SP-E-OUT	VA26A0604-001	2026-01-12	0.0100	0.771
WWTP-E-OUT	Effluent	WWTP-E-OUT	VA26A0124-003	2026-01-05	0.0246	1.81

Notes:

PCDD = polychlorinated dibenzodioxins (dioxins)

PCDF = polychlorinated dibenzofurans (furans)

TEQ = toxic equivalency

Lower bound PCDD/F TEQ is the sum of the toxic equivalency results for the individual PCDD/F parameters. Non-detectable parameters are assigned a value of zero (0).

Upper bound PCDD/F TEQ is the sum of the toxic equivalency results for the individual PCDD/F parameters. Non-detectable parameters are assigned the value of the detection limit.

**Table B-5:
East Catchment Field Measurements Collected During the Monitoring Period (February 8 – 14).**

Parameter			Temp.	Dissolved Oxygen (DO)	Salinity	Turbidity	Estimated TSS ³	pH	Specific Conductivity	Visibility of Sheen
Unit			°C	mg/L	ppt	NTU	mg/L	s.u.	µS/cm	
PE-111578 Discharge Limit			-	-	-	-	25 or 75 ⁶	5.5 - 9.0	-	-
Lowest Applicable Guideline ¹			-	≥8	-	-	- ²	- ²	-	-
Station ID	Water Type	Date								
Influent ⁴										
SP-E-IN	Influent	2026-02-08 11:35	9.4	11.96	0.25	138.83	106.5	8.1	508	No
SP-E-IN	Influent	2026-02-09 8:43	7.5	11.66	0.27	62.00	49.2	6.4	551	No
SP-E-IN	Influent	2026-02-10 17:16	8.1	11.26	0.25	114.06	88.1	7.2	524	No
SP-E-IN	Influent	2026-02-11 15:18	8.1	11.42	0.42	34.00	28.4	7.7	545	No
SP-E-IN	Influent	2026-02-12 12:51	7.6	11.75	0.30	18.54	16.8	8.4	608	No
SP-E-IN	Influent	2026-02-13 9:02	7.6	11.87	0.24	25.19	21.8	7.4	489	No
SP-E-IN	Influent	2026-02-14 12:08	8.6	12.17	0.29	72.76	57.3	7.1	594	No
WWTP-E-IN	Influent	2026-02-09 8:12	7.8	11.57	0.25	323.51	244.3	7.7	524	No
WWTP-E-IN	Influent	2026-02-10 17:21	8.0	11.44	0.27	131.76	101.3	7.4	546	No
WWTP-E-IN	Influent	2026-02-12 9:23	8.0	11.21	0.28	29.59	25.1	7.1	577	No
WWTP-E-IN	Influent	2026-02-13 9:13	7.3	11.86	0.29	307.91	232.6	7.2	593	No
WWTP-E-IN	Influent	2026-02-14 15:26	8.1	11.89	0.26	173.44	132.4	7.3	528	No
Effluent ⁵										
WWTP-E-OUT	Effluent	2026-02-09 8:31	7.9	11.39	0.32	9.18	9.8	6.2	663	No
WWTP-E-OUT	Effluent	2026-02-10 17:27	8.2	8.56	0.52	4.53	6.4	7.0	1043	No
WWTP-E-OUT	Effluent	2026-02-12 15:11	7.9	12.23	0.39	2.92	5.2	6.4	730	No
WWTP-E-OUT	Effluent	2026-02-12 15:11	8.2	12.23	0.28	2.92	5.2	6.4	576	No
WWTP-E-OUT	Effluent	2026-02-13 9:09	7.9	12.59	0.30	2.26	4.7	7.1	621	No
WWTP-E-OUT	Effluent	2026-02-14 15:21	8.1	12.68	0.28	3.05	5.3	7.6	572	No

Notes:

The east catchment did not discharge to Howe Sound during the monitoring period (February 8 – 14). Results above screening values are highlighted for comparative purposes.

Results **underlined in bold italics** exceed the applicable long-term water quality guideline for the protection of marine water aquatic life.

Shaded results exceed the applicable short-term water quality guideline for the protection of marine water aquatic life.

Results in **orange text** exceed the PE-111578 East Sedimentation Pond Discharge Limit.

¹ The lowest applicable guidelines from approved or working BC WQGs, Canadian (CCME) WQGs and Federal WQGs.

² The WQG was not evaluated for parameters with discharge limits.

³ TSS concentration is estimated from field turbidity measurements using a site-specific relationship TSS = 0.7458 * [turbidity as NTU] + 3.

⁴ Daily field measurements for station SP-E-IN were collected from cell 1 of the East Sedimentation Pond. Daily field parameters were not collected at the influent station to the East WWTP (WWTP-E-IN) on February 8 and 11 as the East WWTP was not operated at the time of monitoring.

⁵ There was no discharge at the authorized discharge location (SP-E-OUT) during the monitoring period (February 8 – 14), therefore daily field measurements for SP-E-OUT were not collected on those days. Daily field parameters were not collected at the effluent station to the East WWTP (WWTP-E-OUT) on February 8 and 11 as the East WWTP was not operated at the time of monitoring.

⁶ The PE-111578 discharge limit for TSS is 25 mg/L under dry conditions and 75 mg/L for each day of Wet Conditions and for one day following the end of Wet Conditions.

**Table B-6:
East Catchment Daily Discharge Volumes for the Monitoring Period (February 8 – 14).**

	East Sedimentation Pond Effluent	Transfer to West Sedimentation Pond	East WWTP Treated Effluent (Station WWTP-E-OUT) ²	Discharge to Howe Sound (Station SP-E-OUT)
Units	m ³	m ³	m ³	m ³
PE-111578 Discharge Limit	-	-	1100	- ¹
Date				
2026-02-08	0	0	197	0
2026-02-09	0	0	344	0
2026-02-10	0	1,338	374	0
2026-02-11	0	0	214	0
2026-02-12	0	0	587	0
2026-02-13	0	0	561	0
2026-02-14	0	0	605	0

Notes:

Results in orange text exceed the PE-111578 East Sedimentation Pond Discharge Limit.

¹ As noted in PE-111578 Condition 2.1.4, the annual average authorized discharge rate from the East Sedimentation Pond to Howe Sound was set to 650 m³/day for the purpose of calculating discharge fees as required by the Permit and Approval Fees and Charges Regulation. Therefore, the annual average authorized discharge rate is not evaluated as a discharge limit.

² East WWTP treated effluent was recirculated to the East Sedimentation Pond.

***Appendix C:
West Catchment Monitoring Results***

**Table C-1:
West 2700GPM TSS Settling System Influent and Effluent Analytical Results Received at the Time of Reporting.**

Parameter	Unit	Lowest Applicable Guideline ¹		PE-111578 Discharge Limit	Station 2700GPM-IN	Station W2700T1-OUT	Station W2700T2-OUT	Station W2700T4-OUT
					Influent	Effluent	Effluent	Effluent
					2700GPM-IN	W2700T1-OUT	W2700T2-OUT	W2700T4-OUT
					VA26A3106-002	VA26A3106-003	VA26A3106-004	VA26A3106-005
					2026-02-09 12:39	2026-02-09 11:30	2026-02-09 11:36	2026-02-09 12:13
General Parameters								
pH - Field	pH units	- ²	-	5.5 - 9.0	7.9	7.9	7.9	7.9
Specific Conductivity - Field	µS/cm	-	-	-	267	268	271	267.2
Temperature - Field	°C	-	-	-	7.7	7.6	7.6	7.7
Salinity - Field	ppt	-	-	-	0.13	0.13	0.13	0.13
Turbidity - Field	NTU	-	-	-	25.46	4.99	7.35	5.81
TSS	mg/L	-	-	25 or 75 ⁶	18.4	<3.0	<3.0	<3.0
Dissolved Oxygen - Field	mg/L	≥8	-	-	12.53	13.29	13.08	12.85
Total Hardness	mg/L	-	-	-	51	46.6	46.6	47.6
Dissolved Hardness	mg/L	-	-	-	48.5	47.2	49	50
Anions and Nutrients								
Sulphate	mg/L	-	-	-	64.8	65.8	66.4	64.9
Chloride	mg/L	-	-	-	3.03	3.18	3.14	3.06
Fluoride	mg/L	-	1.5	-	0.06	0.06	0.061	0.06
Ammonia (N-NH ₃)	mg/L	4.7 ³	31 ³	-	<0.0050	<0.0050	<0.0050	0.0073
Nitrite (N-NO ₂)	mg/L	-	-	-	0.0128	0.0096	0.0101	0.0242
Nitrate (N-NO ₃)	mg/L	3.7	339	-	0.123	0.117	0.122	0.11
Total Organic Carbon (TOC)	mg/L	-	-	-	2.66	2.44	2.4	2.12
Dissolved Organic Carbon (DOC)	mg/L	-	-	-	2.31	2.55	2.19	2.53
Total Metals								
Aluminum, total (T-Al)	mg/L	-	-	-	1.18	0.158	0.113	0.109
Antimony, total (T-Sb)	mg/L	-	0.27 ⁴	-	0.00058	0.00057	0.00057	0.00055
Arsenic, total (T-As)	mg/L	0.0125	-	-	0.00137	0.00115	0.00119	0.00111
Barium, total (T-Ba)	mg/L	-	-	-	0.0116	0.00235	0.00249	0.00254
Beryllium, total (T-Be)	mg/L	0.1	-	-	<0.000020	<0.000020	<0.000020	<0.000020
Boron, total (T-B)	mg/L	1.2	-	-	<0.010	<0.010	<0.010	<0.010
Cadmium, total (T-Cd)	mg/L	0.00012	-	-	0.0000152	<0.0000050	<0.0000100	<0.0000100
Chromium, total (T-Cr)	mg/L	-	-	-	0.0007	<0.00050	<0.00050	<0.00050
Cobalt, total (T-Co)	mg/L	-	-	-	0.00033	<0.00010	<0.00010	<0.00010
Copper, total (T-Cu)	mg/L	- ²	- ²	0.0043	0.00282	0.0012	0.00108	0.00158
Iron, total (T-Fe)	mg/L	-	-	-	0.897	0.071	0.044	0.046
Lead, total (T-Pb)	mg/L	- ²	- ²	0.0035	0.000976	0.000234	0.000152	0.000229
Manganese, total (T-Mn)	mg/L	-	-	-	0.0515	0.0218	0.021	0.0237
Molybdenum, total (T-Mo)	mg/L	-	-	-	0.0109	0.0107	0.0108	0.0096
Nickel, total (T-Ni)	mg/L	0.0083	-	-	<0.00050	<0.00050	<0.00050	<0.00050
Selenium, total (T-Se)	mg/L	0.002	-	-	0.000054	0.000091	0.00006	0.000085
Silver, total (T-Ag)	mg/L	0.0005	0.0037	-	<0.000010	<0.000010	<0.000010	<0.000010
Thallium, total (T-Tl)	mg/L	-	-	-	0.000015	0.000012	0.000011	0.000014
Uranium, total (T-U)	mg/L	-	-	-	0.0028	0.00258	0.00245	0.00226
Vanadium, total (T-V)	mg/L	- ²	-	0.0081	0.00235	0.00104	0.00093	0.00071
Zinc, total (T-Zn)	mg/L	- ²	- ²	0.0133	0.0081	<0.0030	<0.0030	0.005
Hexavalent Chromium, total	mg/L	0.0015	-	-	<0.00050	<0.00050	<0.00050	<0.00050
Dissolved Metals								
Cadmium, dissolved (D-Cd)	mg/L	-	-	-	<0.0000100	<0.0000050	<0.0000100	<0.0000050
Copper, dissolved (D-Cu)	mg/L	-	-	-	0.00092	0.00082	0.00083	0.00094
Iron, dissolved (D-Fe)	mg/L	-	-	-	<0.010	<0.010	0.015	0.01
Lead, dissolved (D-Pb)	mg/L	-	-	-	<0.000050	<0.000050	0.000053	0.00008
Manganese, dissolved (D-Mn)	mg/L	-	-	-	0.0207	0.0202	0.0202	0.0233
Nickel, dissolved (D-Ni)	mg/L	-	-	-	<0.00050	<0.00050	<0.00050	<0.00050
Strontium, dissolved (D-Sr)	mg/L	-	-	-	0.0568	0.0587	0.0559	0.0526
Vanadium, dissolved (D-V)	mg/L	-	-	-	0.00084	0.00079	0.00078	0.00052
Zinc, dissolved (D-Zn)	mg/L	-	-	-	0.0017	0.001	<0.0010	0.0024
Polycyclic Aromatic Hydrocarbons (PAHs)								
Acenaphthene	mg/L	0.006	-	-	-	-	-	-
Acridine	mg/L	-	-	-	-	-	-	-
Anthracene	mg/L	-	-	-	-	-	-	-
Benz(a)anthracene	mg/L	-	-	-	-	-	-	-
Benzo(a)pyrene	mg/L	0.00001	-	-	-	-	-	-
Chrysene	mg/L	0.0001	-	-	-	-	-	-
Fluoranthene	mg/L	-	-	-	-	-	-	-
Fluorene	mg/L	0.012	-	-	-	-	-	-
1-methylnaphthalene	mg/L	0.001	-	-	-	-	-	-
2-methylnaphthalene	mg/L	0.001	-	-	-	-	-	-
Naphthalene	mg/L	0.001	-	-	-	-	-	-
Phenanthrene	mg/L	-	-	-	-	-	-	-
Pyrene	mg/L	-	-	-	-	-	-	-
Quinoline	mg/L	-	-	-	-	-	-	-
Volatile Organic Compounds (VOCs)								
Benzene	mg/L	0.11	-	-	-	-	-	-
Ethylbenzene	mg/L	0.25	-	-	-	-	-	-
Methyl-tert-butyl-ether	mg/L	5	0.44	-	-	-	-	-
Styrene	mg/L	-	-	-	-	-	-	-
Toluene	mg/L	0.215	-	-	-	-	-	-
Total Xylenes	mg/L	-	-	-	-	-	-	-
Chlorobenzene	mg/L	0.025	-	-	-	-	-	-
1,2-Dichlorobenzene	mg/L	0.042	-	-	-	-	-	-

Notes:

West catchment influents were not discharged to Howe Sound. Influent results above screening values are only highlighted for comparative purposes.

Non-detect results are screened using the detection limit value.

Results ***underlined in bold italics*** exceed the applicable long-term water quality guideline for the protection of marine water aquatic life.

Shaded results exceed the applicable short-term water quality guideline for the protection of marine water aquatic life.

Results in **orange text** exceed the PE-111578 West Sedimentation Pond Discharge Limit.

The West Catchment intermittently discharged during the monitoring period (February 8 – 14) on February 8, 9, 12 and 13.

¹ The lowest applicable guidelines from approved or working BC WQGs, Canadian (CCME) WQGs and Federal WQGs for marine waters.

² The WQG was not evaluated for parameters with discharge limits.

³ The BC WQG for total ammonia is salinity, pH and temperature dependent; see Tables 27E and 27F in BC WQG guidance document.

⁴ The working BC WQG for trivalent antimony [SB(III)] is 0.27 mg/L and is applied to total antimony results.

⁵ When MeHg ≤ 0.5% of total Hg, the BC WQG = 0.00002 mg/L. The Canadian WQG = 0.000016 mg/L.

⁶ The PE-111578 discharge limit for TSS is 25 mg/L under dry conditions and 75 mg/L for each day of Wet Conditions and for one day following the end of Wet Conditions.

**Table C-2:
West 2700GPM TSS Settling System Influent and Effluent Analytical Results Received at the Time of Reporting.**

Parameter	Unit	Lowest Applicable Guideline ¹		PE-111578 Discharge Limit	Station W2700T1-OUT	Station W2700T2-OUT	Station W2700T4-OUT
					Effluent	Effluent	Effluent
		W2700T1-OUT	W2700T2-OUT		W2700T4-OUT		
		VA26A3338-001	VA26A3338-002		VA26A3338-003		
		Long Term	Short Term		2026-02-11 14:17	2026-02-11 14:29	2026-02-11 14:39
General Parameters							
pH - Field	pH units	- ²	-	5.5 - 9.0	7.6	7.8	7.6
Specific Conductivity - Field	µS/cm	-	-	-	324.3	325	307.5
Temperature - Field	°C	-	-	-	8.4	8.8	8.3
Salinity - Field	ppt	-	-	-	0.16	0.16	0.15
Turbidity - Field	NTU	-	-	-	2.15	3.58	2.93
TSS	mg/L	-	-	25 or 75 ⁶	<3.0	<3.0	<3.0
Dissolved Oxygen - Field	mg/L	≥8	-	-	11.91	12.79	12.03
Total Hardness	mg/L	-	-	-	60.8	59	54.3
Dissolved Hardness	mg/L	-	-	-	59	61.4	54.7
Anions and Nutrients							
Sulphate	mg/L	-	-	-	-	-	-
Chloride	mg/L	-	-	-	-	-	-
Fluoride	mg/L	-	1.5	-	-	-	-
Ammonia (N-NH ₃)	mg/L	4.7-7.2 ³	31-48 ³	-	-	-	-
Nitrite (N-NO ₂)	mg/L	-	-	-	-	-	-
Nitrate (N-NO ₃)	mg/L	3.7	339	-	-	-	-
Total Organic Carbon (TOC)	mg/L	-	-	-	-	-	-
Dissolved Organic Carbon (DOC)	mg/L	-	-	-	-	-	-
Total Metals							
Aluminum, total (T-Al)	mg/L	-	-	-	0.0517	0.051	0.0714
Antimony, total (T-Sb)	mg/L	-	0.27 ⁴	-	0.00078	0.00077	0.00068
Arsenic, total (T-As)	mg/L	0.0125	-	-	0.00134	0.00129	0.00122
Barium, total (T-Ba)	mg/L	-	-	-	0.0031	0.00277	0.00249
Beryllium, total (T-Be)	mg/L	0.1	-	-	<0.000020	<0.000020	<0.000020
Boron, total (T-B)	mg/L	1.2	-	-	0.014	0.014	<0.010
Cadmium, total (T-Cd)	mg/L	0.00012	-	-	<0.0000100	<0.0000100	<0.0000100
Chromium, total (T-Cr)	mg/L	-	-	-	0.00056	0.00054	<0.00050
Cobalt, total (T-Co)	mg/L	-	-	-	<0.00010	<0.00010	<0.00010
Copper, total (T-Cu)	mg/L	- ²	- ²	0.0043	0.00107	0.00151	0.002
Iron, total (T-Fe)	mg/L	-	-	-	0.019	0.019	0.028
Lead, total (T-Pb)	mg/L	- ²	- ²	0.0035	0.000078	0.000144	0.000184
Manganese, total (T-Mn)	mg/L	-	-	-	0.0236	0.024	0.0254
Molybdenum, total (T-Mo)	mg/L	-	-	-	0.0184	0.0178	0.0132
Nickel, total (T-Ni)	mg/L	0.0083	-	-	<0.00050	<0.00050	<0.00050
Selenium, total (T-Se)	mg/L	0.002	-	-	<0.000150	<0.000150	<0.000100
Silver, total (T-Ag)	mg/L	0.0005	0.0037	-	<0.000010	<0.000010	<0.000010
Thallium, total (T-Tl)	mg/L	-	-	-	<0.000020	<0.000020	<0.000020
Uranium, total (T-U)	mg/L	-	-	-	0.00317	0.00317	0.0026
Vanadium, total (T-V)	mg/L	- ²	-	0.0081	0.00102	0.00098	0.00057
Zinc, total (T-Zn)	mg/L	- ²	- ²	0.0133	<0.0030	<0.0030	<0.0030
Hexavalent Chromium, total	mg/L	0.0015	-	-	0.00052	<0.00050	<0.00050
Dissolved Metals							
Cadmium, dissolved (D-Cd)	mg/L	-	-	-	<0.0000100	<0.0000100	<0.0000100
Copper, dissolved (D-Cu)	mg/L	-	-	-	0.00096	0.0011	0.00103
Iron, dissolved (D-Fe)	mg/L	-	-	-	<0.010	<0.010	<0.010
Lead, dissolved (D-Pb)	mg/L	-	-	-	<0.000050	<0.000050	0.000063
Manganese, dissolved (D-Mn)	mg/L	-	-	-	0.0231	0.0239	0.0245
Nickel, dissolved (D-Ni)	mg/L	-	-	-	<0.00050	<0.00050	<0.00050
Strontium, dissolved (D-Sr)	mg/L	-	-	-	0.0778	0.08	0.0663
Vanadium, dissolved (D-V)	mg/L	-	-	-	0.00099	0.00093	0.00051
Zinc, dissolved (D-Zn)	mg/L	-	-	-	0.0012	0.0016	0.0017
Polycyclic Aromatic Hydrocarbons (PAHs)							
Acenaphthene	mg/L	0.006	-	-	-	-	-
Acridine	mg/L	-	-	-	-	-	-
Anthracene	mg/L	-	-	-	-	-	-
Benz(a)anthracene	mg/L	-	-	-	-	-	-
Benzo(a)pyrene	mg/L	0.00001	-	-	-	-	-
Chrysene	mg/L	0.0001	-	-	-	-	-
Fluoranthene	mg/L	-	-	-	-	-	-
Fluorene	mg/L	0.012	-	-	-	-	-
1-methylnaphthalene	mg/L	0.001	-	-	-	-	-
2-methylnaphthalene	mg/L	0.001	-	-	-	-	-
Naphthalene	mg/L	0.001	-	-	-	-	-
Phenanthrene	mg/L	-	-	-	-	-	-
Pyrene	mg/L	-	-	-	-	-	-
Quinoline	mg/L	-	-	-	-	-	-
Volatile Organic Compounds (VOCs)							
Benzene	mg/L	0.11	-	-	-	-	-
Ethylbenzene	mg/L	0.25	-	-	-	-	-
Methyl-tert-butyl-ether	mg/L	5	0.44	-	-	-	-
Styrene	mg/L	-	-	-	-	-	-
Toluene	mg/L	0.215	-	-	-	-	-
Total Xylenes	mg/L	-	-	-	-	-	-
Chlorobenzene	mg/L	0.025	-	-	-	-	-
1,2-Dichlorobenzene	mg/L	0.042	-	-	-	-	-

Notes:

West catchment influents were not discharged to Howe Sound. Influent results above screening values are only highlighted for comparative purposes.

Non-detect results are screened using the detection limit value.

Results **underlined in bold italics** exceed the applicable long-term water quality guideline for the protection of marine water aquatic life.

Shaded results exceed the applicable short-term water quality guideline for the protection of marine water aquatic life.

Results in **orange text** exceed the PE-111578 West Sedimentation Pond Discharge Limit.

The West Catchment intermittently discharged during the monitoring period (February 8 – 14) on February 8, 9, 12 and 13.

¹ The lowest applicable guidelines from approved or working BC WQGs, Canadian (CCME) WQGs and Federal WQGs for marine waters.

² The WQG was not evaluated for parameters with discharge limits.

³ The BC WQG for total ammonia is salinity, pH and temperature dependent; see Tables 27E and 27F in BC WQG guidance document.

⁴ The working BC WQG for trivalent antimony [SB(III)] is 0.27 mg/L and is applied to total antimony results.

⁵ When MeHg ≤ 0.5% of total Hg, the BC WQG = 0.00002 mg/L. The Canadian WQG = 0.000016 mg/L.

⁶ The PE-111578 discharge limit for TSS is 25 mg/L under dry conditions and 75 mg/L for each day of Wet Conditions and for one day following the end of Wet Conditions.

**Table C-3:
West Sedimentation Pond Influent and Effluent Analytical Results Received at the Time of Reporting.**

Parameter	Unit	Lowest Applicable Guideline ¹		PE-111578 Discharge Limit	Station SP-W-IN	Station SP-W-OUT	Station SP-W-OUT
					Influent	Effluent	Effluent
		SP-W-IN	SP-W-OUT		SP-W-OUT-DUP		
		VA26A3106-001 2026-02-09 9:00	VA26A3106-006 2026-02-09 11:07		VA26A3106-007 2026-02-09 11:07		
		Long Term	Short Term				
General Parameters							
pH - Field	pH units	- ²	-	5.5 - 9.0	7.3	7.9	7.9
Specific Conductivity - Field	µS/cm	-	-	-	269	264	264
Temperature - Field	°C	-	-	-	7.5	7.8	7.8
Salinity - Field	ppt	-	-	-	0.13	0.13	0.13
Turbidity - Field	NTU	-	-	-	28.24	3.79	3.88
TSS	mg/L	-	-	25 or 75 ⁶	33.8	<3.0	-
Dissolved Oxygen - Field	mg/L	≥8	-	-	13	13.38	13.42
Total Hardness	mg/L	-	-	-	50.3	47.3	-
Dissolved Hardness	mg/L	-	-	-	48.4	47.9	-
Anions and Nutrients							
Sulphate	mg/L	-	-	-	64.6	65.7	-
Chloride	mg/L	-	-	-	3.06	3.13	-
Fluoride	mg/L	-	1.5	-	0.062	0.06	-
Ammonia (N-NH ₃)	mg/L	4.7-18 ³	31-121 ³	-	0.0054	<0.0050	-
Nitrite (N-NO ₂)	mg/L	-	-	-	0.0121	0.0103	-
Nitrate (N-NO ₃)	mg/L	3.7	339	-	0.128	0.119	-
Total Organic Carbon (TOC)	mg/L	-	-	-	2.59	2.39	-
Dissolved Organic Carbon (DOC)	mg/L	-	-	-	2.71	2.36	-
Total Metals							
Aluminum, total (T-Al)	mg/L	-	-	-	1.49	0.122	0.123
Antimony, total (T-Sb)	mg/L	-	0.27 ⁴	-	0.00061	0.00055	0.00055
Arsenic, total (T-As)	mg/L	0.0125	-	-	0.00141	0.0012	0.00117
Barium, total (T-Ba)	mg/L	-	-	-	0.0132	0.00205	0.00226
Beryllium, total (T-Be)	mg/L	0.1	-	-	0.000028	<0.000020	<0.000020
Boron, total (T-B)	mg/L	1.2	-	-	<0.010	<0.010	<0.010
Cadmium, total (T-Cd)	mg/L	0.00012	-	-	0.0000187	<0.0000100	<0.0000100
Chromium, total (T-Cr)	mg/L	-	-	-	0.00078	<0.00050	<0.00050
Cobalt, total (T-Co)	mg/L	-	-	-	0.00045	<0.00010	<0.00010
Copper, total (T-Cu)	mg/L	- ²	- ²	0.0043	0.00191	0.00799	0.00466
Iron, total (T-Fe)	mg/L	-	-	-	1.24	0.053	0.054
Lead, total (T-Pb)	mg/L	- ²	- ²	0.0035	0.000933	0.000518	0.000342
Manganese, total (T-Mn)	mg/L	-	-	-	0.0636	0.021	0.0214
Molybdenum, total (T-Mo)	mg/L	-	-	-	0.011	0.0107	0.011
Nickel, total (T-Ni)	mg/L	0.0083	-	-	<0.00050	<0.00050	<0.00050
Selenium, total (T-Se)	mg/L	0.002	-	-	0.000056	0.000069	0.000061
Silver, total (T-Ag)	mg/L	0.0005	0.0037	-	<0.000010	<0.000010	<0.000010
Thallium, total (T-Tl)	mg/L	-	-	-	0.000017	0.000011	0.000011
Uranium, total (T-U)	mg/L	-	-	-	0.00272	0.00256	0.00268
Vanadium, total (T-V)	mg/L	- ²	-	0.0081	0.00277	0.00097	0.00097
Zinc, total (T-Zn)	mg/L	- ²	- ²	0.0133	0.0092	0.0041	<0.0030
Hexavalent Chromium, total	mg/L	0.0015	-	-	<0.00050	<0.00050	-
Dissolved Metals							
Cadmium, dissolved (D-Cd)	mg/L	-	-	-	<0.0000100	<0.0000050	<0.0000100
Copper, dissolved (D-Cu)	mg/L	-	-	-	0.00067	0.0007	0.00075
Iron, dissolved (D-Fe)	mg/L	-	-	-	<0.010	0.011	<0.010
Lead, dissolved (D-Pb)	mg/L	-	-	-	<0.000050	<0.000050	<0.000050
Manganese, dissolved (D-Mn)	mg/L	-	-	-	0.0204	0.0225	0.0227
Nickel, dissolved (D-Ni)	mg/L	-	-	-	<0.00050	<0.00050	<0.00050
Strontium, dissolved (D-Sr)	mg/L	-	-	-	0.0582	0.0534	0.056
Vanadium, dissolved (D-V)	mg/L	-	-	-	0.00084	0.00056	0.00055
Zinc, dissolved (D-Zn)	mg/L	-	-	-	<0.0010	<0.0010	<0.0010
Polycyclic Aromatic Hydrocarbons (PAHs)							
Acenaphthene	mg/L	0.006	-	-	-	-	-
Acridine	mg/L	-	-	-	-	-	-
Anthracene	mg/L	-	-	-	-	-	-
Benz(a)anthracene	mg/L	-	-	-	-	-	-
Benzo(a)pyrene	mg/L	0.00001	-	-	-	-	-
Chrysene	mg/L	0.0001	-	-	-	-	-
Fluoranthene	mg/L	-	-	-	-	-	-
Fluorene	mg/L	0.012	-	-	-	-	-
1-methylnaphthalene	mg/L	0.001	-	-	-	-	-
2-methylnaphthalene	mg/L	0.001	-	-	-	-	-
Naphthalene	mg/L	0.001	-	-	-	-	-
Phenanthrene	mg/L	-	-	-	-	-	-
Pyrene	mg/L	-	-	-	-	-	-
Quinoline	mg/L	-	-	-	-	-	-
Volatile Organic Compounds (VOCs)							
Benzene	mg/L	0.11	-	-	-	-	-
Ethylbenzene	mg/L	0.25	-	-	-	-	-
Methyl-tert-butyl-ether	mg/L	5	0.44	-	-	-	-
Styrene	mg/L	-	-	-	-	-	-
Toluene	mg/L	0.215	-	-	-	-	-
Total Xylenes	mg/L	-	-	-	-	-	-
Chlorobenzene	mg/L	0.025	-	-	-	-	-
1,2-Dichlorobenzene	mg/L	0.042	-	-	-	-	-

Notes:

West catchment influents were not discharged to Howe Sound. Influent results above screening values are only highlighted for comparative purposes.

Non-detect results are screened using the detection limit value.

Results **underlined in bold italics** exceed the applicable long-term water quality guideline for the protection of marine water aquatic life.

Shaded results exceed the applicable short-term water quality guideline for the protection of marine water aquatic life.

Results in **orange text** exceed the PE-111578 West Sedimentation Pond Discharge Limit.

The West Catchment intermittently discharged during the monitoring period (February 8 – 14) on February 8, 9, 12 and 13.

¹ The lowest applicable guidelines from approved or working BC WQGs, Canadian (CCME) WQGs and Federal WQGs for marine waters.

² The WQG was not evaluated for parameters with discharge limits.

³ The BC WQG for total ammonia is salinity, pH and temperature dependent; see Tables 27E and 27F in BC WQG guidance document.

⁴ The working BC WQG for trivalent antimony [SB(III)] is 0.27 mg/L and is applied to total antimony results.

⁵ When MeHg ≤ 0.5% of total Hg, the BC WQG = 0.00002 mg/L. The Canadian WQG = 0.000016 mg/L.

⁶ The PE-111578 discharge limit for TSS is 25 mg/L under dry conditions and 75 mg/L for each day of Wet Conditions and for one day following the end of Wet Conditions.

**Table C-4:
West Catchment Methylmercury and Corresponding Total Mercury Results Received at the Time of Reporting.**

Parameter					Total Methylmercury	Total Mercury
Unit					µg/L	µg/L
Lowest Applicable Guideline ¹					0.0001 ²	0.0043-0.010 ^{3,4}
Station	Water Type	Sample ID	Lab ID	Sampling Date		
Influent						
SP-W-IN	Influent	SP-W-IN	VA26A3106-001	2026-02-09	0.000031	0.00313
2700GPM-IN	Influent	2700GPM-IN	VA26A3106-002	2026-02-09	0.000034	0.00176
Effluent						
SP-W-OUT	Effluent	SP-W-OUT	VA26A3106-006	2026-02-09	0.000020	0.00123
W2700T1-OUT	Effluent	W2700T1-OUT	VA26A3106-003	2026-02-09	0.000026	0.00131
W2700T2-OUT	Effluent	W2700T2-OUT	VA26A3106-004	2026-02-09	0.000028	0.00119
W2700T4-OUT	Effluent	W2700T4-OUT	VA26A3106-005	2026-02-09	<0.000020	0.00100

Notes:

West catchment influents were not discharged to Howe Sound. Results above screening values are only highlighted for comparative purposes. Non-detect results are screened using the detection limit value.

Results ***underlined in bold italics*** exceed the applicable long-term water quality guideline for the protection of marine aquatic life.

¹ The lowest applicable guidelines from approved or working BC WQGs, Canadian (CCME) WQGs and Federal WQGs.

² From BC Ambient Water Quality Guidelines for Mercury Overview Report. The methylmercury concentration threshold of 0.0001 µg/L (0.1 ng/L) is indicated as a WQG for the protection of wildlife and is set at a concentration that protects fish from mercury bioaccumulation to a level that may harm wildlife that consume fish.

³ CCME guideline for total mercury = 0.016 µg/L.

⁴ When MeHg ≤ 0.5% of total Hg, BC WQG = 0.02 µg/L. When MeHg > 0.5% of total Hg, BC WQG = 0.0001/(MeHg/Total Hg). Detection limit values are used to calculate the WQG for result reported as not detected.

**Table C-5:
West Catchment Dioxin and Furan Toxicity Equivalency Quantity (TEQ) Results Received at the Time of Reporting.**

Parameter					Lower Bound PCDD/F TEQ	Upper Bound PCDD/F TEQ
Unit					pg/L	pg/L
Station	Water Type	Sample ID	Lab ID	Sampling Date		
Influent						
SP-W-IN	Influent	SP-W-IN	VA26A0079-001	2026-01-04	2.85	5.16
2700GPM-IN	Influent	W2700-IN	VA26A0079-002	2026-01-04	2.05	4.41
Effluent						
SP-W-OUT	Effluent	SP-W-OUT	VA26A0079-005	2026-01-04	0.0222	1.86
SP-W-OUT	Effluent	SP-W-OUT-DUP	VA26A0079-006	2026-01-04	0	2.15

Notes:

PCDD = polychlorinated dibenzodioxins (dioxins)

PCDF = polychlorinated dibenzofurans (furans)

TEQ = toxic equivalency

Lower bound PCDD/F TEQ is the sum of the toxic equivalency results for the individual PCDD/F parameters. Non-detectable parameters are assigned a value of zero (0).

Upper bound PCDD/F TEQ is the sum of the toxic equivalency results for the individual PCDD/F parameters. Non-detectable parameters are assigned the value of the detection limit.

**Table C-6:
West Catchment Field Measurements Collected During the Monitoring Period (February 8 – 14).**

Parameter	Temperature	Dissolved Oxygen (DO)	Salinity	Turbidity	Estimated TSS ³	pH	Specific Conductivity	Visibility of Sheen		
Unit	°C	mg/L	ppt	NTU	mg/L	s.u.	µS/cm			
PE-111578 Discharge Limit	-	-	-	-	25 or 75 ⁶	5.5 - 9.0	-	-		
Lowest Applicable Guideline¹	-	≥8	-	-	- ²	- ²	-	-		
Station ID	Water Type	Date								
Influent ⁴										
SP-W-IN	Influent	2026-02-08 11:11	8.5	12.26	0.070	31.57	26.5	7.6	146	No
SP-W-IN	Influent	2026-02-09 9:00	7.5	13.00	0.13	28.24	24.1	7.3	269	No
SP-W-IN	Influent	2026-02-10 15:15	9.5	12.03	0.18	85.47	66.7	7.2	369	No
SP-W-IN	Influent	2026-02-11 15:30	8.0	12.42	0.15	7.34	8.5	7.6	308	No
SP-W-IN	Influent	2026-02-12 16:09	7.6	13.26	0.15	3.21	5.4	7.5	314	No
SP-W-IN	Influent	2026-02-13 8:19	7.2	11.94	0.23	428.95	322.9	7.2	467	No
SP-W-IN	Influent	2026-02-14 14:48	8.8	12.51	0.21	94.75	73.7	7.5	428	No
2700GPM-IN	Influent	2026-02-09 12:39	7.7	12.53	0.13	25.46	22.0	7.9	267	No
2700GPM-IN	Influent	2026-02-10 15:21	8.5	11.76	0.15	152.22	116.5	7.5	318	No
2700GPM-IN	Influent	2026-02-11 14:52	8.8	12.17	0.15	13.12	12.8	7.6	313	No
2700GPM-IN	Influent	2026-02-13 8:49	7.4	11.97	0.25	71.92	56.6	7.5	515	No
2700GPM-IN	Influent	2026-02-14 14:52	8.5	12.10	0.21	67.51	53.3	7.8	429	No
Effluent ⁵										
SP-W-OUT	Effluent	2026-02-08 11:17	7.9	12.76	0.15	2.86	5.1	7.7	317	No
SP-W-OUT	Effluent	2026-02-09 11:07	7.8	13.38	0.13	3.79	5.8	7.9	264	No
SP-W-OUT	Effluent	2026-02-10 15:25	7.4	12.44	0.13	5.57	7.2	7.7	274	No
SP-W-OUT	Effluent	2026-02-13 8:25	7.4	12.75	0.23	5.19	6.9	7.3	470	No

Notes:

West catchment influents for February 8 – 14 were not discharged to Howe Sound. Results above screening values are only highlighted for comparative purposes.

Results ***underlined in bold italics*** exceed the applicable long-term water quality guideline for the protection of marine water aquatic life.

Shaded results exceed the applicable short-term water quality guideline for the protection of marine water aquatic life.

Results in **orange text** exceed the PE-111578 West Sedimentation Pond Discharge Limit.

¹ The lowest applicable guidelines from approved or working BC WQGs, Canadian (CCME) WQGs and Federal WQGs.

² The WQG was not evaluated for parameters with discharge limits.

³ TSS concentration is estimated from field turbidity measurements using a site-specific relationship TSS = 0.7458 * [turbidity as NTU] + 3.

⁴ Daily field measurements for station SP-W-IN were collected from cell 1 of the West Sedimentation Pond.

⁵ As described in Section 1.1, when there is surplus water, West Sedimentation Pond clarified effluent from the individual 2700GPM trains is directed to SP-W-OUT for discharge. 2700GPM clarified effluent from all six trains was intermittently discharged to Howe Sound at the authorized discharge location (SP-W-OUT) on February 8, 9, 12 and 13. Daily field measurements were not collected at SP-W-OUT on February 12 as there was no discharge to Howe Sound at the time of monitoring. Field measurements collected February 10 at SP-W-OUT were collected from residual water in the sampling port as there was no discharge to Howe Sound at the time of monitoring.

⁶ The PE-111578 discharge limit for TSS is 25 mg/L under dry conditions and 75 mg/L for each day of Wet Conditions and for one day following the end of Wet Conditions.

**Table C-7:
West Catchment Daily Discharge Volumes for the Monitoring Period (February 8 – 14).**

	West Sedimentation Pond Effluent	West TSS Settling System (2700GPM) Clarified Effluent (Station 2700GPM-OUT) ³	Water Reclaimed for Construction Purposes (Station 2700GPM-OUT)	West WWTP Treated Effluent ¹ (Station WWTP-W-OUT)	Discharge to Howe Sound (Station SP-W-OUT)
Unit	m ³	m ³	m ³	m ³	m ³
PE-111578 Discharge Limit	-	-	-	120	- ²
Date					
2026-02-08	0	656	0	0	93
2026-02-09	0	2,079	0	0	922
2026-02-10	0	2,026	0	0	0
2026-02-11	0	2,237	0	0	0
2026-02-12	0	2,328	0	0	938
2026-02-13	0	2,926	0	0	950
2026-02-14	0	2,811	0	0	0

Notes:

Results in orange text exceed the PE-111578 West Sedimentation Pond Discharge Limit.

¹ The West WWTP is not being operated therefore discharges are not expected from this facility.

² As noted in PE-111578 Condition 2.2.4, the annual average authorized discharge rate from the West Sedimentation Pond to Howe Sound was set to 310 m³/day for the purpose of calculating discharge fees as required by the Permit and Approval Fees and Charges Regulation. Therefore, the annual average authorized discharge rate is not evaluated as a discharge limit.

³ Clarified effluent from the 2700GPM TSS settling system is recirculated to the West Sedimentation Pond, discharged to Howe Sound or reclaimed for construction purposes based on operational considerations. Daily discharge volumes from station 2700GPM-OUT are a sum of all active treatment trains.

***Appendix D:
Non-Contact Water Diversion Ditch Outlets
Monitoring Results***

**Table D-1:
Summary of Non-Contact Water Diversion Ditch Outlet Quality Results Received at the Time of Reporting.**

Parameter	Unit	Lowest Applicable Guideline ^{1,2}		Station OUT-01	Station OUT-02	Station OUT-06
				Non-contact Water Diversion Ditch Outlet	Non-contact Water Diversion Ditch Outlet	Non-contact Water Diversion Ditch Outlet
				OUT-01	OUT-02	OUT-06
				VA26A2456-001	VA26A2456-002	VA26A2456-003
		Long Term	Short Term	2026-02-02 10:59	2026-02-02 11:13	2026-02-02 11:25
General Parameters						
pH - Field	pH units	6.5 - 9.0	-	7.88	6.89	6.85
Specific Conductivity - Field	µS/cm	-	-	12	15	44
Temperature - Field	°C	-	-	6.8	7.1	7.2
Salinity - Field	ppt	-	-	0	0.01	0.02
Turbidity - Field	NTU	-	-	0.42	1.65	3.06
TSS	mg/L	-	-	<3.0	<3.0	<3.0
Dissolved Oxygen - Field	mg/L	>=8	>=5	12.15	12.16	12.12
Total Hardness	mg/L	-	-	3.73	4.41	19.9
Dissolved Hardness	mg/L	-	-	3.59	3.48	19
Anions and Nutrients						
Sulphate ²	mg/L	128	-	1.28	1.48	2.31
Chloride	mg/L	120	600	<0.50	<0.50	<0.50
Fluoride ²	mg/L	-	0.400-0.685	<0.020	<0.020	<0.020
Ammonia (N-NH ₃) ²	mg/L	0.0340-15.3	0.681-23.6	<0.0050	<0.0050	<0.0050
Nitrite (N-NO ₂) ²	mg/L	0.200	0.6	<0.0010	<0.0010	<0.0010
Nitrate (N-NO ₃)	mg/L	3	32.8	0.0847	0.0367	0.129
Total Organic Carbon (TOC)	mg/L	-	-	4.1	4.08	5.26
Total Inorganic Carbon (DOC)	mg/L	-	-	4.04	4.55	4.98
Total Metals						
Aluminum, total (T-Al) ²	mg/L	0.103-2.80	-	0.16	0.22	0.23
Antimony, total (T-Sb)	mg/L	0.074	-	<0.00010	<0.00010	0.00013
Arsenic, total (T-As)	mg/L	0.005	-	<0.00010	<0.00010	0.00017
Barium, total (T-Ba)	mg/L	1	-	0.00255	0.00272	0.00617
Beryllium, total (T-Be)	mg/L	0.00013	-	<0.000020	<0.000020	<0.000020
Boron, total (T-B)	mg/L	1.2	29	<0.010	<0.010	<0.010
Cadmium, total (T-Cd) ²	mg/L	0.000036-0.000042	0.00011-0.00041	<0.0000050	<0.0000050	0.0000054
Chromium, total (T-Cr) ³	mg/L	0.001	-	<0.00050	<0.00050	<0.00050
Cobalt, total (T-Co) ²	mg/L	0.000389-0.000778	-	<0.00010	<0.00010	<0.00010
Copper, total (T-Cu)	mg/L	-	-	0.00053	0.00062	0.00087
Iron, total (T-Fe)	mg/L	0.3	1	0.021	0.04	0.066
Lead, total (T-Pb)	mg/L	-	-	<0.000050	0.000094	0.000178
Manganese, total (T-Mn) ²	mg/L	0.768	0.816	0.00089	0.00212	0.00254
Molybdenum, total (T-Mo)	mg/L	0.073	46	0.000249	0.000542	0.00078
Nickel, total (T-Ni) ²	mg/L	0.0250	-	<0.00050	<0.00050	<0.00050
Selenium, total (T-Se)	mg/L	0.001	-	<0.000050	<0.000050	<0.000050
Silver, total (T-Ag)	mg/L	0.00012	-	<0.000010	<0.000010	<0.000010
Thallium, total (T-Tl)	mg/L	0.0008	-	<0.000010	<0.000010	<0.000010
Uranium, total (T-U)	mg/L	0.0085	0.033	0.000035	0.000122	0.000103
Vanadium, total (T-V)	mg/L	0.12	-	<0.00050	<0.00050	0.00056
Zinc, total (T-Zn)	mg/L	-	-	<0.0030	<0.0030	0.0048
Hexavalent Chromium, total	mg/L	0.001	-	-	-	-
Dissolved Metals						
Cadmium, dissolved (D-Cd) ²	mg/L	0.000019-0.000065	0.000038-0.00011	<0.0000050	<0.0000050	<0.0000050
Copper, dissolved (D-Cu) ²	mg/L	0.000381-0.00382	0.00250-0.0122	0.00055	0.00053	0.00079
Iron, dissolved (D-Fe)	mg/L	-	0.35	0.017	0.017	0.014
Lead, dissolved (D-Pb) ²	mg/L	0.00221-0.00656	-	<0.000050	<0.000050	0.000054
Manganese, dissolved (D-Mn) ²	mg/L	0.200-0.350	1.97	0.0017	0.0017	0.00181
Nickel, dissolved (D-Ni) ²	mg/L	0.000900-0.00150	0.0148-0.0191	<0.00050	<0.00050	<0.00050
Strontium, dissolved (D-Sr)	mg/L	2.5	-	0.00548	0.00535	0.0281
Vanadium, dissolved (D-V)	mg/L	-	-	<0.00050	<0.00050	<0.00050
Zinc, dissolved (D-Zn) ²	mg/L	0.00245-0.0144	0.0105-0.0300	0.0014	<0.0010	0.004
Polycyclic Aromatic Hydrocarbons (PAHs)						
Acenaphthene	mg/L	0.0058	-	-	-	-
Acridine	mg/L	0.003	-	-	-	-
Anthracene	mg/L	0.000012	-	-	-	-
Benz(a)anthracene	mg/L	0.000018	-	-	-	-
Benzo(a)pyrene	mg/L	0.000001	-	-	-	-
Chrysene	mg/L	-	-	-	-	-
Fluoranthene	mg/L	0.000004	-	-	-	-
Fluorene	mg/L	0.003	-	-	-	-
1-methylnaphthalene	mg/L	-	-	-	-	-
2-methylnaphthalene	mg/L	-	-	-	-	-
Naphthalene	mg/L	0.001	0.001	-	-	-
Phenanthrene	mg/L	0.0003	-	-	-	-
Pyrene	mg/L	0.00002	-	-	-	-
Quinoline	mg/L	0.0034	-	-	-	-
Volatile Organic Compounds (VOCs)						
Benzene	mg/L	0.04	-	-	-	-
Ethylbenzene	mg/L	0.09	-	-	-	-
Methyl-tert-butyl-ether	mg/L	10	3.4	-	-	-
Styrene	mg/L	0.072	-	-	-	-
Toluene	mg/L	0.0005	-	-	-	-
Total Xylenes	mg/L	0.03	-	-	-	-
Chlorobenzene	mg/L	-	-	-	-	-
1,2-Dichlorobenzene	mg/L	-	-	-	-	-

Notes:

Non-detect results are screened using the detection limit value.

Results **underlined in bold italics** exceed the applicable long-term water quality guideline for the protection of freshwater aquatic life.

Shaded results exceed the applicable short-term water quality guideline for the protection of freshwater aquatic life.

¹ The lowest applicable guidelines from approved or working BC WQGs, Canadian (CCME) WQGs and Federal WQGs.² BC WQG or CWQG indicated to be variable are calculated from sample-specific measurements for temperature, field pH, total hardness and dissolved organic carbon (DOC) content.³ The approved BC WQG for hexavalent chromium [Cr(VI)] is 0.001 mg/L and 0.0089 mg/L for trivalent chromium [Cr(III)]. The more conservative criteria for Cr(VI) is applied to total chromium results.

The lowest applicable guidelines are shown in the table; however, water quality data was screened to all applicable guidelines.

**Table D-2:
Non-contact Water Diversion Ditch Outlet Methylmercury and Corresponding Total Mercury Results Received at the Time of Reporting.**

Parameter					Total Methylmercury	Total Mercury
Unit					µg/L	µg/L
Lowest Applicable Guideline ¹					0.0001 ²	0.012-0.020 ^{3,4}
Station	Description	Sample ID	Lab ID	Sampling Date		
OUT-01	Non-Contact Water Diversion Ditch Outlet	OUT-01	VA26A2456-001	2026-02-02	0.000028	0.00323
OUT-02	Non-Contact Water Diversion Ditch Outlet	OUT-02	VA26A2456-002	2026-02-02	0.000022	0.00367
OUT-06	Non-Contact Water Diversion Ditch Outlet	OUT-06	VA26A2456-003	2026-02-02	<0.000020	0.00508

Notes:

Results ***underlined in bold italics*** exceed the applicable long-term water quality guideline for the protection of freshwater aquatic life.

¹ The lowest applicable guidelines from approved or working BC WQGs, Canadian (CCME) WQGs and Federal WQGs.

² From BC Ambient Water Quality Guidelines for Mercury Overview Report. The methylmercury concentration threshold of 0.0001 µg/L (0.1 ng/L) is indicated as a WQG for the protection of wildlife and is set at a concentration that protects fish from mercury bioaccumulation to a level that may harm wildlife that consume fish.

³ CCME guideline for total mercury = 0.026 µg/L.

⁴ When MeHg ≤ 0.5% of total Hg, BC WQG = 0.02 µg/L. When MeHg > 0.5% of total Hg, BC WQG = 0.0001/(MeHg/Total Hg). Detection limit values are used to calculate the WQG for result reported as not detected.

Non-detect results are screened using the detection limit value.